

# Declaration of Conformity

In Accordance with ANSI/ISEA 125-2014 and ANSI/ASSP Z359.7-2019



Alexander Andrew, Inc. 1306 S. Alameda St Compton, CA 90221 (800) 719-4619

Declaration #

B1017213a

Declaration Date

5/13/2025

Tested Item #

19104DQCSM

1910 FBH 4D Climbing Non-Belted, Small/Medium, QC Legs and Chest

**Additional Items Conforming Under this Declaration:**

19103DQC2X3X 19103DQCXS 19104DQCXS 1910FDQCSM 1910QCCLX 1910F3DQCXS 1910F3DQC2X3X 1910FQCLX  
19103DQCLX 19104DQC2X3X 1910FDQC2X3X 1910FDQCXS 1910QCSCM 1910F3DQCSCM 1910FQCXS 1910FQC2X3X  
19103DQCSM 19104DQCLX 1910FDQCLX 1910QC2X3X 1910QCXS 1910F3DQCLX 1910FQCSCM

Alexander Andrew, Inc. declares that the product(s) listed above is in conformity with the requirements of the following product standard(s):

**ANSI Z359.11-2021**

**Conformity Assessment Method in accordance with ANSI/ISEA 125-2014**

Level 1

Level 2

Level 3

**Level 1:** FallTech Lab  
Outside the Scope of  
ISO/IEC Standard 17025:2017

**Level 2:** FallTech Lab  
Within the Scope of  
ISO/IEC Standard 17025:2017

**Level 3:** Independent 3rd Party Lab accredited to  
ISO/IEC Standard 17025:2017

Supporting  
Documentation

PC-3253

Authorized Signature

Name

Zachary Winters

Title

Engineering Manager

Date

5/13/2025



International Accreditation Service, Inc  
3060 Saturn St, Ste 100  
Brea, CA 92821 +1 562-364-8201

FallTech Lab - TL-594  
ISO/IEC 17025:2017  
Alexander Andrew Inc dba FallTech

### FallTech Test Report

<b>Test Report No.</b>	PC-3253	<b>Rpt. Date</b>	10/17/2024	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Zachary Winters	<b>Test Specification(s)</b>		ANSI Z359.11-2021: 4.3.3, 4.3.4, 4.3.5, 4.3.6			
<b>Part No.</b>	19104DQC5M	<b>Part No. Revision</b>			A		
<b>Part Description</b>	FT-1910 FBH 4D Climbing Non-Belted, Small/Medium, QC Legs and Chest						
<b>Test Request No.</b>	PC-3253	<b>Date Complete</b>			10/16/2024		
<b>Test Operator(s)</b>	Yesbet Sierra / Jay Sponholz						

### Material/Sample Identification

Sample ID	Description
8152448	FT-1910 FBH 4D Climbing Non-Belted, Small/Medium, QC Legs and Chest
8152454	FT-1910 FBH 4D Climbing Non-Belted, Small/Medium, QC Legs and Chest
8152455	FT-1910 FBH 4D Climbing Non-Belted, Small/Medium, QC Legs and Chest
8152452	FT-1910 FBH 4D Climbing Non-Belted, Small/Medium, QC Legs and Chest
8152451	FT-1910 FBH 4D Climbing Non-Belted, Small/Medium, QC Legs and Chest
8152453	FT-1910 FBH 4D Climbing Non-Belted, Small/Medium, QC Legs and Chest
8064492	FT-1910 FBH 4D Climbing Non-Belted, Small/Medium, QC Legs and Chest
8152450	FT-1910 FBH 4D Climbing Non-Belted, Small/Medium, QC Legs and Chest
8152457	FT-1910 FBH 4D Climbing Non-Belted, Small/Medium, QC Legs and Chest
8152456	FT-1910 FBH 4D Climbing Non-Belted, Small/Medium, QC Legs and Chest
8064490	FT-1910 FBH 4D Climbing Non-Belted, Small/Medium, QC Legs and Chest
8064502	FT-1910 FBH 4D Climbing Non-Belted, Small/Medium, QC Legs and Chest
8064503	FT-1910 FBH 4D Climbing Non-Belted, Small/Medium, QC Legs and Chest
8064506	FT-1910 FBH 4D Climbing Non-Belted, Small/Medium, QC Legs and Chest
8064493	FT-1910 FBH 4D Climbing Non-Belted, Small/Medium, QC Legs and Chest
8064500	FT-1910 FBH 4D Climbing Non-Belted, Small/Medium, QC Legs and Chest
8064489	FT-1910 FBH 4D Climbing Non-Belted, Small/Medium, QC Legs and Chest
8064507	FT-1910 FBH 4D Climbing Non-Belted, Small/Medium, QC Legs and Chest

### Test Summary

Test Specification	Test Criteria		Test Result	Pass/Fail
ANSI Z359.11-2021 4.3.5 (Dorsal D-ring)	Static Strength	3600 Lbf $\geq$ 1 Minute	3652.6 Lbf	Pass
	Hold Test Torso	Shall Not Release Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear > 1"	Did Not Tear Through	Pass
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.5 (Dorsal D-ring)	Static Strength	3600 Lbf $\geq$ 1 Minute	3653.1 Lbf	Pass
	Hold Test Torso	Shall Not Release Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear > 1"	Did Not Tear Through	Pass
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.5 (Dorsal D-ring)	Static Strength	3600 Lbf $\geq$ 1 Minute	3657.2 Lbf	Pass
	Hold Test Torso	Shall Not Release Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear > 1"	Did Not Tear Through	Pass
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear	Pass

### FallTech Test Report

<b>Test Report No.</b>	PC-3253	<b>Rpt. Date</b>	10/17/2024	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Zachary Winters	<b>Test Specification(s)</b>	ANSI Z359.11-2021: 4.3.3, 4.3.4, 4.3.5, 4.3.6				
<b>Part No.</b>	19104DQC5M	<b>Part No. Revision</b>	A				
<b>Part Description</b>	FT-1910 FBH 4D Climbing Non-Belted, Small/Medium, QC Legs and Chest						
<b>Test Request No.</b>	PC-3253	<b>Date Complete</b>	10/16/2024				

### Test Summary Continued

Test Specification	Test Criteria	Test Result	Pass/Fail	
ANSI Z359.11-2021 4.3.5 (Sternal D-ring)	Static Strength	3600 Lbf $\geq$ 1 Minute	3660.0 Lbf	Pass
	Hold Test Torso	Shall Not Release Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear > 1"	Did Not Tear Through	Pass
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.5 (Sternal D-ring)	Static Strength	3600 Lbf $\geq$ 1 Minute	3639.7 Lbf	Pass
	Hold Test Torso	Shall Not Release Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear > 1"	Did Not Tear Through	Pass
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.5 (Sternal D-ring)	Static Strength	3600 Lbf $\geq$ 1 Minute	3644.0 Lbf	Pass
	Hold Test Torso	Shall Not Release Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear > 1"	Did Not Tear Through	Pass
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.5 (Side D-rings)	Static Strength	3600 Lbf $\geq$ 1 Minute	3680.9 Lbf	Pass
	Hold Test Torso	Shall Not Release Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear > 1"	Did Not Tear Through	Pass
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.5 (Side D-rings)	Static Strength	3600 Lbf $\geq$ 1 Minute	3664.4 Lbf	Pass
	Hold Test Torso	Shall Not Release Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear > 1"	Did Not Tear Through	Pass
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.5 (Side D-rings)	Static Strength	3600 Lbf $\geq$ 1 Minute	3658.8 Lbf	Pass
	Hold Test Torso	Shall Not Release Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear > 1"	Did Not Tear Through	Pass
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear	Pass

### FallTech Test Report

<b>Test Report No.</b>	PC-3253	<b>Rpt. Date</b>	10/17/2024	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Zachary Winters	<b>Test Specification(s)</b>		ANSI Z359.11-2021: 4.3.3, 4.3.4, 4.3.5, 4.3.6			
<b>Part No.</b>	19104DQC5M	<b>Part No. Revision</b>			A		
<b>Part Description</b>	FT-1910 FBH 4D Climbing Non-Belted, Small/Medium, QC Legs and Chest						
<b>Test Request No.</b>	PC-3253	<b>Date Complete</b>			10/16/2024		

### Test Summary Continued

Test Specification	Test Criteria		Test Result	Pass/Fail
ANSI Z359.11-2021 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load $\geq 3600$ Lbf	4228.9 Lbf	Pass
	Fall Arrest	Shall Not Release Torso	Did Not Release	Pass
	Post Drop Angle	Angle at Rest $\leq 30^\circ$	2.5°	Pass
	Impact Indicator	One Indicator Shall Deploy	Permanently Deployed	Pass
	Harness Stretch	Shall Not Exceed 18"	11.4"	Pass
ANSI Z359.11-2021 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load $\geq 3600$ Lbf	4220.1 Lbf	Pass
	Fall Arrest	Shall Not Release Torso	Did Not Release	Pass
	Post Drop Angle	Angle at Rest $\leq 30^\circ$	3.3°	Pass
	Impact Indicator	One Indicator Shall Deploy	Permanently Deployed	Pass
	Harness Stretch	Shall Not Exceed 18"	12.9"	Pass
ANSI Z359.11-2021 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load $\geq 3600$ Lbf	4157.5 Lbf	Pass
	Fall Arrest	Shall Not Release Torso	Did Not Release	Pass
	Post Drop Angle	Angle at Rest $\leq 30^\circ$	4.3°	Pass
	Impact Indicator	One Indicator Shall Deploy	Permanently Deployed	Pass
	Harness Stretch	Shall Not Exceed 18"	10.8"	Pass
ANSI Z359.11-2021 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact $\geq 3,600$ Lbf or 72" Free Fall	72" Free fall 2255.3 Lbf	Pass
	Fall Arrest	Shall Not Release Torso	Did Not Release	Pass
	Post Drop Angle	Angle at Rest $\leq 30^\circ$	3.1°	Pass
	Impact Indicator	One Indicator Shall Deploy	Permanently Deployed	Pass
ANSI Z359.11-2021 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact $\geq 3,600$ Lbf or 72" Free Fall	72" Free fall 2326.5 Lbf	Pass
	Fall Arrest	Shall Not Release Torso	Did Not Release	Pass
	Post Drop Angle	Angle at Rest $\leq 30^\circ$	4.5°	Pass
	Impact Indicator	One Indicator Shall Deploy	Permanently Deployed	Pass
ANSI Z359.11-2021 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact $\geq 3,600$ Lbf or 72" Free Fall	72" Free fall 2485.1 Lbf	Pass
	Fall Arrest	Shall Not Release Torso	Did Not Release	Pass
	Post Drop Angle	Angle at Rest $\leq 30^\circ$	3.8°	Pass
	Impact Indicator	One Indicator Shall Deploy	Permanently Deployed	Pass

### FallTech Test Report

<b>Test Report No.</b>	PC-3253	<b>Rpt. Date</b>	10/17/2024	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Zachary Winters	<b>Test Specification(s)</b>		ANSI Z359.11-2021: 4.3.3, 4.3.4, 4.3.5, 4.3.6			
<b>Part No.</b>	19104DQCSM	<b>Part No. Revision</b>			A		
<b>Part Description</b>	FT-1910 FBH 4D Climbing Non-Belted, Small/Medium, QC Legs and Chest						
<b>Test Request No.</b>	PC-3253	<b>Date Complete</b>			10/16/2024		

### Test Summary Continued

Test Specification	Test Criteria		Test Result	Pass/Fail
ANSI Z359.11-2021 4.3.3	Dynamic Performance Sternal D-ring (Feet First)	Peak Impact Load $\geq 3600$ Lbf	3807.5 Lbf	Pass
	Fall Arrest	Shall Not Release Torso	Did Not Release	Pass
	Post Drop Angle	Angle at Rest $\leq 50^\circ$	26.7°	Pass
	Impact Indicator	One Indicator Shall Deploy	Permanently Deployed	Pass
	Harness Stretch	Shall Not Exceed 18"	11.5"	Pass
ANSI Z359.11-2021 4.3.3	Dynamic Performance Sternal D-ring (Feet First)	Peak Impact Load $\geq 3600$ Lbf	3889.1 Lbf	Pass
	Fall Arrest	Shall Not Release Torso	Did Not Release	Pass
	Post Drop Angle	Angle at Rest $\leq 50^\circ$	28.7°	Pass
	Impact Indicator	One Indicator Shall Deploy	Permanently Deployed	Pass
	Harness Stretch	Shall Not Exceed 18"	11.1"	Pass
ANSI Z359.11-2021 4.3.3	Dynamic Performance Sternal D-ring (Feet First)	Peak Impact Load $\geq 3600$ Lbf	3500.2 Lbf	Pass
	Fall Arrest	Shall Not Release Torso	Did Not Release	Pass
	Post Drop Angle	Angle at Rest $\leq 50^\circ$	26.9°	Pass
	Impact Indicator	One Indicator Shall Deploy	Permanently Deployed	Pass
	Harness Stretch	Shall Not Exceed 18"	10.6"	Pass
ANSI Z359.11-2021 4.3.6	Fall Arrest Indicator Test (Doral D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
ANSI Z359.11-2021 4.3.6	Fall Arrest Indicator Test (Doral D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
ANSI Z359.11-2021 4.3.6	Fall Arrest Indicator Test (Doral D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
ANSI Z359.11-2021 4.3.6	Fall Arrest Indicator Test (Sternal D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
ANSI Z359.11-2021 4.3.6	Fall Arrest Indicator Test (Sternal D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
ANSI Z359.11-2021 4.3.6	Fall Arrest Indicator Test (Sternal D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass

### Conclusion

Based upon the samples provided to the Lab: FallTech P/N 19104DQCSM Rev. A meets the requirements of ANSI Z359.11-2021
---

### Report Signatories and Approval

Lab Quality Manager		Date	10/17/2024
---------------------	---	------	------------