

FallTech SteelGrip Cable HLL Kit with Pass-Through Anchors

Specification Sheet | SKU 602XA | FallTech

Features

- Complete 60' Temporary Cable HLL system.
- 3/8" galvanized steel cable with one-end terminated and thimble.
- Includes 2 web pass-through sling anchors.
- Features 1 stainless steel coil energy absorber and 2 connecting carabiners.
- In-line tension indicator included with 2 galvanized steel shackles.
- System also includes wire rope clips and tensioning turnbuckle.



Technical Specifications

Type	With sling anchors
SKU	602XA
Static Strength	5,000 lb min.
OSHA User Capacity	310 lb max. per user; 2 users max. per single span
Cable	3/8" galvanized steel; 5,000 lb min. static strength
Sling Anchors	Polyester webbing with plated alloy steel D-rings; 5,000 lb min. static strength
Carabiners	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength
Available Configurations	60230A (30 ft), 60260A (60 ft), 602100A (100 ft)
Standards	Cable HLL System meets OSHA 1926.502 and 1910.140 regulations
Warranty	FallTech 2-year limited warranty against defects in materials and workmanship

Fall Protection Distributors, LLC | standingseamroofanchor.com | 863-703-4522 | Distributor spec sheet compiled from FallTech published data.