

FallTech SteelGrip Cable HLL Kit with I-Beam Stanchions

Specification Sheet | SKU 603XK | FallTech

Features

- Complete 60' Single-span Temporary Cable HLL System.
- Includes two I-beam stanchions with 4" to 24" clamping range.
- 3/8" galvanized steel cable with one-end terminated and thimble.
- Features 1 stainless steel coil energy absorber and 2 connecting carabiners.
- In-line tension indicator included with 2 galvanized steel shackles.
- System also includes wire rope clips and tensioning turnbuckle.



Technical Specifications

Type	With stanchions
SKU	603XK
Static Strength	5,000 lb min.
OSHA User Capacity	310 lb max. per user; 2 users max. per single span
Cable	3/8" galvanized steel; 5,000 lb min. static strength
Stanchions	Plated carbon steel post, base and clamp; 8,000 lb min. static strength
Carabiners	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength
Available Configurations	6033024 (30 ft, 4 to 24 in), 6036012 (60 ft, 4 to 12 in), 6036018 (60 ft, 4 to 18 in), 6036024 (60 ft, 4 to 24 in), 60310012 (100 ft, 4 to 12 in), 60310018 (100 ft, 4 to 18 in), 60310024 (100 ft, 4 to 24 in)
Standards	Cable HLL System meets OSHA 1926.502 and 1910.140 regulations
Warranty	FallTech 2-year limited warranty against defects in materials and workmanship

Fall Protection Distributors, LLC | standingseamroofanchor.com | 863-703-4522 | Distributor spec sheet compiled from FallTech published data.