

# FallTech SteelGrip Temporary Cable HLL Assembly

Specification Sheet | SKU 620X | FallTech

## Features

- SteelGrip Cable HLL Assembly, no anchors.
- 3/8" galvanized steel cable with one-end terminated and thimble.
- Features 1 stainless steel coil energy absorber and 2 connecting carabiners.
- In-line tension indicator included with 2 galvanized steel shackles.
- System also includes wire rope clips and tensioning turnbuckle.
- User-supplied end-point anchors required.



## Technical Specifications

<b>Type</b>	60' assembly without anchors
<b>SKU</b>	620X
<b>Static Strength</b>	5,000 lb min.
<b>OSHA User Capacity</b>	310 lb max. per user; 2 users max. per single span
<b>Cable</b>	3/8" galvanized steel; 5,000 lb min. static strength
<b>Energy Absorber</b>	304 Stainless Steel
<b>Carabiners</b>	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength
<b>Available Configurations</b>	620030 (30 ft), 620060 (60 ft), 620100 (100 ft), 620130 (130 ft)
<b>Standards</b>	Cable HLL System meets OSHA 1926.502 and 1910.140 regulations
<b>Warranty</b>	FallTech 2-year limited warranty against defects in materials and workmanship

Fall Protection Distributors, LLC | [standingseamroofanchor.com](http://standingseamroofanchor.com) | 863-703-4522 | Distributor spec sheet compiled from FallTech published data.