

FallTech SteelGrip Plus Cable HLL with Ratchet Tensioner

Part Number(s): 620030R, 620060R, 620100R | Brand: FallTech | Product Specification Sheet

Features

- SteelGrip Plus™ Cable HLL Assembly, no anchors
- 3/8" galvanized steel cable with one-end terminated and thimbled.
- Features 1 stainless steel coil energy absorber and 2 connecting carabiners
- In-line tension indicator included with 2 galvanized steel shackles
- System also includes wire rope clips and ratchet strap tensioner
- User-supplied end-point anchors required
- SteelGrip Plus™ Patent Pending



Specifications

| | |
|---------------------------|---|
| Description | 3/8" galvanized steel cable |
| Static Strength | 5,000 lb min. |
| OSHA User Capacity | 310 lb max. per user; 2 users max. per single span |
| Cable | 3/8" galvanized steel; 5,000 lb min. static strength |
| Energy Absorber | 304 Stainless Steel |
| Carabiners | Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength |
| Unit Weight | 24.6 lb |
| Relevant Standards | Cable HLL System meets OSHA 1926.502 and 1910.140 regulations |

Distributed by Fall Protection Distributors, LLC, an authorized FallTech dealer. standingseamroofanchor.com | 863-703-4522.
Specifications from FallTech published product data. Always follow the FallTech instruction manual.