

FallTech Rescue and Descent Crane Kit with Sealed Barrel

Specification Sheet | SKU 6813K | FallTech

Features

- 7/16" sheathed-core kernmantle rope lifeline resists moisture and abrasion for longer life.
- Integral triple-mode lifting capability includes handwheel, ratcheting handle and power drill adapter.
- Telescoping Ratchet lifting handle adjusts from 12" to 18" for unmatched rescue lifting leverage.
- Bi-directional design provides shuttle operation for multiple successive descending users.
- Rope lifeline features aluminum alloy connectors for lighter weight.
- Device features integral belay hooks and swiveling aluminum attachment carabiner.



Technical Specifications

Type	Crane Rescue Kit
SKU	6813K
Max Descent Height	524' for 2 users
Max Descent Load	440 lb for 2 users
Descent Speed	2.6' per second for 1 user
Cumulative Descent Distance	25,200' or 48 descents with 220 lb
Rope	7/16" kernmantle polyamide blend
Connectors	Aluminum alloy; 5,000 lb static strength with 3,600 lb gate strength
Housing	Powder coated aluminum
Available Configurations	6813150K (150 ft), 6813300K (300 ft)
Standards	ANSI Z359.4-2013
Warranty	FallTech 2-year limited warranty against defects in materials and workmanship

Fall Protection Distributors, LLC | standingseamroofanchor.com | 863-703-4522 | Distributor spec sheet compiled from FallTech published data.