

# FallTech Rescue and Descent Worksite Kit with Storage Bag

Specification Sheet | SKU 6814K | FallTech

## Features

- 7/16" sheathed-core kernmantle rope lifeline resists moisture and abrasion for longer life.
- Integral triple-mode lifting capability includes handwheel, ratcheting handle and power drill adapter.
- Telescoping Ratchet lifting handle adjusts from 12" to 18" for unmatched rescue lifting leverage.
- Bi-directional design provides shuttle operation for multiple successive descending users.
- Rope lifeline features aluminum alloy connectors for lighter weight.
- Device features integral belay hooks and swiveling aluminum attachment carabiner.



## Technical Specifications

<b>Type</b>	Worksite Rescue Kit
<b>SKU</b>	6814K
<b>Max Descent Height</b>	524' for 2 users
<b>Max Descent Load</b>	440 lb for 2 users
<b>Descent Speed</b>	2.6' per second for 1 user
<b>Cumulative Descent Distance</b>	25,200' or 48 descents with 220 lb
<b>Rope</b>	7/16" kernmantle polyamide blend
<b>Connectors</b>	Aluminum alloy; 5,000 lb min. static strength with 3,600 lb gate strength
<b>Housing</b>	Powder coated aluminum
<b>Available Configurations</b>	6814150K (150 ft), 6814300K (300 ft), 6814400K (400 ft), 6814500K (500 ft)
<b>Standards</b>	ANSI Z359.4-2013
<b>Warranty</b>	FallTech 2-year limited warranty against defects in materials and workmanship

Fall Protection Distributors, LLC | [standingseamroofanchor.com](http://standingseamroofanchor.com) | 863-703-4522 | Distributor spec sheet compiled from FallTech published data.