

# FallTech 7006B Tradesman Plus 1D Standard Non-belted Harness

Specification Sheet | SKU 7006B | FallTech Body Wear

## Features

- Features an integral tri-layer padded shoulder yoke to provide breathable user comfort across the shoulders and upper back.
- The proprietary dorsal attachment sleeve supports effortless addition of personal SRLs without extra carabiners or adapters.
- Plated alloy steel low-profile spring tension roller torso adjusters provide simple upper-body adjustment.
- The dorsal D-ring, quick-connect chest, and mating buckle leg closures are all durably plated alloy steel.
- The quick-connect chest buckle features visual indicators showing positive connection before you leave the ground.
- Polyester webbing rated to 5,000 lb min. static strength carries the load path through the entire harness.



## Technical Specifications

<b>Type</b>	Non-Belted Full Body Harness
<b>SKU</b>	7006B
<b>Family</b>	Tradesman Plus
<b>D-Rings</b>	1 (Dorsal)
<b>Closures</b>	Mating Buckle Legs and Quick-connect Chest
<b>Webbing</b>	Polyester; 5,000 lb min. static strength
<b>D-Ring Hardware</b>	Plated alloy steel; 5,000 lb min. static strength
<b>Buckles and Adjusters</b>	Plated alloy steel; 3,372 lb min. static strength
<b>Static Strength</b>	3,600 lb min.
<b>ANSI User Capacity</b>	130 to 310 lb max.
<b>OSHA User Capacity</b>	130 to 425 lb max.
<b>Standards</b>	ANSI Z359.11-2014; OSHA 1926.502 and 1910.140; CSA Z259.10-2018
<b>Available Configurations</b>	7006B (UniFit), 7006B3X (3X)
<b>Warranty</b>	FallTech 2-year manufacturer warranty, honored through Fall Protection Distributors