

FallTech 7009B Tradesman Plus 3D Standard Non-belted Harness

Specification Sheet | SKU 7009B | FallTech Body Wear

Features

- Three plated alloy steel D-rings pair everyday fall arrest with hip-based work positioning connections.
- Features an integral tri-layer padded shoulder yoke to provide breathable user comfort across the shoulders and upper back.
- The proprietary dorsal attachment sleeve supports effortless addition of personal SRLs without extra carabiners or adapters.
- Plated alloy steel low-profile spring tension roller torso adjusters provide simple upper-body adjustment.
- The quick-connect chest buckle features visual indicators showing positive connection before you leave the ground.
- Polyester webbing rated to 5,000 lb min. static strength carries the load path through the entire harness.



Technical Specifications

Type	Non-Belted Full Body Harness
SKU	7009B
Family	Tradesman Plus
D-Rings	3 (Dorsal, Hip)
Closures	Mating Buckle Legs and Quick-connect Chest
Webbing	Polyester; 5,000 lb min. static strength
D-Ring Hardware	Plated alloy steel; 5,000 lb min. static strength
Buckles and Adjusters	Plated alloy steel; 3,372 lb min. static strength
Static Strength	3,600 lb min.
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 425 lb max.
Standards	ANSI Z359.11-2014; OSHA 1926.502 and 1910.140; CSA Z259.10-2018
Available Configurations	7009BSM (S/M), 7009B (UniFit), 7009BX/2X (XL/2X), 7009B2X (2X)
Warranty	FallTech 2-year manufacturer warranty, honored through Fall Protection Distributors