

# FallTech 7015LXLX Hi-Vis Lime Construction-grade Vest, 1D Harness

Specification Sheet | SKU 7015LXLX | FallTech Body Wear

## Features

- Includes high-visibility safety vest with integrated Contractor #7015-series harness
- Harness features dorsal D-ring for fall arrest with mating buckle leg and chest closures.
- Day-bright mesh and solid fabric construction with secondary reflectivity
- Vest features four front pockets and internal donning fasteners and loops for removable integration with harness straps
- Complies with ANSI Z359.11-2014



## Technical Specifications

<b>Product Type</b>	Non-Belted Full Body Harness
<b>D-Rings</b>	1 D-Ring: Dorsal
<b>Adjustment</b>	Mating Buckle Leg Adjustment
<b>Webbing</b>	Polyester; 5,000 lb min. static strength
<b>D-Ring Hardware</b>	Plated alloy steel; 5,000 lb min. static strength
<b>Buckles and Adjusters</b>	Plated alloy steel; 3,372 lb min. static strength
<b>Static Strength</b>	3,600 lb min.
<b>ANSI User Capacity</b>	130 to 310 lb max.
<b>OSHA User Capacity</b>	130 to 425 lb max.
<b>Standards</b>	ANSI Z359.11-2014; OSHA 1926.502 and 1910.140; CSA Z259.10-2018
<b>Available Configurations</b>	7015SML (S/M Vest with UniFit Harness), 7015LXL (L/XL Vest with UniFit Harness), 70152X3XL (2X/2X Vest with 2X/3X Harness)
<b>Warranty</b>	FallTech 2-Year Manufacturer Warranty