FallTech 7016BFD Contractor+ Front 1D Standard Non-belted Harness

Specification Sheet | SKU 7016BFD | FallTech Body Wear

Features

- Proprietary dorsal attachment sleeve supports effortless addition of personal SRLs
- Plated alloy steel low-profile spring tension roller torso adjusters provide simple adjustment
- Breathable padded air-mesh shoulder yoke delivers added user comfort
- Paired lanyard parking keepers provide balanced function for single and twin-leg personal SRLs
- Plated alloy steel dorsal and sternal D-rings with mating buckle chest and tongue buckle leg closures
- Features tongue buckle leg connections with 7 grommeted leg adjustment positions for a wide range of fit
- Complies with ANSI Z359.11-2014

Technical Specifications

Product Type	Non-Belted Full Body Harness
D-Rings	2 D-Rings: Dorsal, Sternal
Adjustment	Tongue Buckle Leg Adjustment
Webbing	Polyester; 5,000 lb min. static strength
D-Ring Hardware	Plated alloy steel; 5,000 lb min. static strength
Buckles and Adjusters	Plated alloy steel; 3,372 lb min. static strength
Static Strength	3,600 lb min.
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 425 lb max.
Standards	ANSI Z359.11-2014; OSHA 1926.502 and 1910.140; CSA Z259.10-2018
Available Configurations	7016BFDXS (XS), 7016BFDS (Small), 7016BFDM (Medium), 7016BFDL (Large), 7016BFDXL (XL), 7016BFD2X (2X), 7016BFD3X (3X)
Warranty	FallTech 2-Year Manufacturer Warranty