

# FallTech 7016PCX Contractor 1D Coated Web Harness

Specification Sheet | SKU 7016PCX | FallTech Body Wear

## Features

- Heavy-duty urethane-coated polyester web construction throughout torso and legs
- Well-suited for paint and chemical processing applications and generally harsh environments
- Plated alloy steel mating buckle torso adjusters deliver economical fit
- Features tongue buckle leg connections with 7 grommets leg adjustment positions for a wide range of fit
- Paired lanyard parking keepers provide balanced function for single and double-leg lanyards
- Plated alloy steel dorsal D-ring with mating buckle chest and tongue buckle leg closures
- Complies with ANSI Z359.11-2014



## Technical Specifications

<b>Product Type</b>	Non-Belted Full Body Harness
<b>D-Rings</b>	1 D-Ring: Dorsal
<b>Adjustment</b>	Tongue Buckle Leg Adjustment
<b>Webbing</b>	Polyester; 5,000 lb min. static strength
<b>D-Ring Hardware</b>	Plated alloy steel; 5,000 lb min. static strength
<b>Buckles and Adjusters</b>	Plated alloy steel; 3,372 lb min. static strength
<b>Static Strength</b>	3,600 lb min.
<b>ANSI User Capacity</b>	130 to 310 lb max.
<b>OSHA User Capacity</b>	130 to 425 lb max.
<b>Standards</b>	ANSI Z359.11-2014; OSHA 1926.502 and 1910.140
<b>Available Configurations</b>	7016PC (UniFit (S, M, L)), 7016XLPC (XL)
<b>Warranty</b>	FallTech 2-Year Manufacturer Warranty

Fall Protection Distributors, LLC | standingseamroofanchor.com | 863-703-4522 | Distributor spec sheet compiled from FallTech published data.