

# Declaration of Conformity

In Accordance with ANSI/ISEA 125-2014 and ANSI/ASSP Z359.7-2019



Alexander Andrew, Inc. 1306 S. Alameda St Compton, CA 90221 (800) 719-4619

Declaration #

B0804158a

Declaration Date

8/4/2021

Tested Item #

7018

**Contractor FBH 3D Standard Non-Belted UniFit TB Legs  
MB Chest**

**Additional Items Conforming Under this Declaration:**

7016	70162X3XL	70163X	7016LXL	7016SML	7016X/2X	7016XS	70182X
70182X3XL	70182X3XO	70183X	7018LXL	7018LXO	7018SML	7018SMO	7018XL
7018XS	A7016	A7016X/2X	UA70162X3XL	UA7016LXL	UA7016SML	7016T	

Alexander Andrew, Inc. declares that the product(s) listed above is in conformity with the requirements of the following product standard(s):

**ANSI Z359.11-2021**

**Conformity Assessment Method in accordance with ANSI/ISEA 125-2014**

Level 1

Level 2

Level 3

**Level 1:** FallTech Lab  
Outside the Scope of  
ISO/IEC Standard 17025:2005

**Level 2:** FallTech Lab  
Within the Scope of  
ISO/IEC Standard 17025:2005

**Level 3:** Independent 3rd Party Lab  
accredited to  
ISO/IEC Standard 17025:2005

Supporting  
Documentation

PC-2301

Authorized Signature

Name

Zachary Winters

Title

Engineering Manager

Date

1/26/2024



International Accreditation Service, Inc  
3060 Saturn St, Ste 100  
Brea, CA 92821 +1 562-364-8201

FallTech Lab - TL-594  
ISO/IEC 17025:2017  
Alexander Andrew Inc dba FallTech

## FallTech Test Report

<b>Test Report No.</b>	PC-2301	<b>Rpt. Date</b>	8/4/2021	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Dan Redden	<b>Test Specification(s)</b>	ANSI Z359.11-2021: 4.3.5, 4.3.3, 4.3.4, 4.3.6				
<b>Part No.</b>	7018	<b>Part No. Revision</b>	E				
<b>Part Description</b>	Contractor FBH 3D Standard Non-Belted UniFit TB Legs MB Chest						
<b>Test Request No.</b>	PC-2301	<b>Date Complete</b>	7/27/2021				
<b>Test Operator(s)</b>	Yesbet Sierra / Jay Sponholz						

### Material/Sample Identification

Sample ID	Description
249994	Contractor FBH 3D Standard Non-Belted UniFit TB Legs MB Chest
250207	Contractor FBH 3D Standard Non-Belted UniFit TB Legs MB Chest
251688	Contractor FBH 3D Standard Non-Belted UniFit TB Legs MB Chest
250355	Contractor FBH 3D Standard Non-Belted UniFit TB Legs MB Chest
251221	Contractor FBH 3D Standard Non-Belted UniFit TB Legs MB Chest
249981	Contractor FBH 3D Standard Non-Belted UniFit TB Legs MB Chest
249940	Contractor FBH 3D Standard Non-Belted UniFit TB Legs MB Chest
249889	Contractor FBH 3D Standard Non-Belted UniFit TB Legs MB Chest
249899	Contractor FBH 3D Standard Non-Belted UniFit TB Legs MB Chest
250097	Contractor FBH 3D Standard Non-Belted UniFit TB Legs MB Chest
250219	Contractor FBH 3D Standard Non-Belted UniFit TB Legs MB Chest
249799	Contractor FBH 3D Standard Non-Belted UniFit TB Legs MB Chest
250264	Contractor FBH 3D Standard Non-Belted UniFit TB Legs MB Chest
249869	Contractor FBH 3D Standard Non-Belted UniFit TB Legs MB Chest
250274	Contractor FBH 3D Standard Non-Belted UniFit TB Legs MB Chest

### Test Summary

Test Specification	Test Criteria	Test Result	Pass/Fail	
ANSI Z359.11-2021 4.3.5	Static Strength (Dorsal D-ring)	3600 Lbf $\geq$ 1 Minute	3635.2 Lbf	Pass
	Static Strength (Dorsal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass



## FallTech Test Report

<b>Test Report No.</b>	PC-2301	<b>Rpt. Date</b>	8/4/2021	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Dan Redden	<b>Test Specification(s)</b>	ANSI Z359.11-2021: 4.3.5, 4.3.3, 4.3.4, 4.3.6				
<b>Part No.</b>	7018	<b>Part No. Revision</b>	E				
<b>Part Description</b>	Contractor FBH 3D Standard Non-Belted UniFit TB Legs MB Chest						
<b>Test Request No.</b>	PC-2301	<b>Date Complete</b>	7/27/2021				

### Test Summary (Continued)

Test Specification	Test Criteria		Test Result	Pass/Fail
ANSI Z359.11-2021 4.3.5	Static Strength (Dorsal D-ring)	3600 Lbf $\geq$ 1 Minute	3637.1 Lbf	Pass
	Static Strength (Dorsal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.5	Static Strength (Dorsal D-ring)	3600 Lbf $\geq$ 1 Minute	3631.0 Lbf	Pass
	Static Strength (Dorsal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.5	Static Strength (Side D-rings)	3600 Lbf $\geq$ 1 Minute	3648.3 Lbf	Pass
	Static Strength (Side D-rings)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.5	Static Strength (Side D-rings)	3600 Lbf $\geq$ 1 Minute	3634.2 Lbf	Pass
	Static Strength (Side D-rings)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass

## FallTech Test Report

<b>Test Report No.</b>	PC-2301	<b>Rpt. Date</b>	8/4/2021	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Dan Redden	<b>Test Specification(s)</b>	ANSI Z359.11-2021: 4.3.5, 4.3.3, 4.3.4, 4.3.6				
<b>Part No.</b>	7018	<b>Part No. Revision</b>	E				
<b>Part Description</b>	Contractor FBH 3D Standard Non-Belted UniFit TB Legs MB Chest						
<b>Test Request No.</b>	PC-2301	<b>Date Complete</b>	7/27/2021				

### Test Summary (Continued)

Test Specification	Test Criteria	Test Result	Pass/Fail	
ANSI Z359.11-2021 4.3.5	Static Strength (Side D-rings)	3600 Lbf $\geq$ 1 Minute	3657.9 Lbf	Pass
	Static Strength (Side D-rings)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load $\geq$ 3600 Lbf	4549.9 Lbf	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Remain Suspended for $\geq$ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Angle at Rest $\leq$ 30°	1.8°	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Stretch Shall Not Exceed 18"	8.4"	Pass
ANSI Z359.11-2021 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load $\geq$ 3600 Lbf	4448.7 Lbf	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Remain Suspended for $\geq$ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Angle at Rest $\leq$ 30°	1.7°	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Stretch Shall Not Exceed 18"	7.2"	Pass

## FallTech Test Report

<b>Test Report No.</b>	PC-2301	<b>Rpt. Date</b>	8/4/2021	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Dan Redden	<b>Test Specification(s)</b>	ANSI Z359.11-2021: 4.3.5, 4.3.3, 4.3.4, 4.3.6				
<b>Part No.</b>	7018	<b>Part No. Revision</b>	E				
<b>Part Description</b>	Contractor FBH 3D Standard Non-Belted UniFit TB Legs MB Chest						
<b>Test Request No.</b>	PC-2301	<b>Date Complete</b>	7/27/2021				

### Test Summary (Continued)

Test Specification	Test Criteria	Test Result	Pass/Fail	
ANSI Z359.11-2021 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load ≥ 3600 Lbf	4743.6 Lbf	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Angle at Rest ≤ 30°	1.3°	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Stretch Shall Not Exceed 18"	7.6"	Pass
ANSI Z359.11-2021 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact ≥ 3,600 Lbf or 72" Free Fall	72" Free fall 3884.8 Lbf	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Angle at Rest ≤ 30°	2.1°	Pass
	Dynamic Performance Dorsal D-ring (Head First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
ANSI Z359.11-2021 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact ≥ 3,600 Lbf or 72" Free Fall	72" Free fall 4097.9 Lbf	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Angle at Rest ≤ 30°	7.1°	Pass
	Dynamic Performance Dorsal D-ring (Head First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass

## FallTech Test Report

<b>Test Report No.</b>	PC-2301	<b>Rpt. Date</b>	8/4/2021	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Dan Redden	<b>Test Specification(s)</b>	ANSI Z359.11-2021: 4.3.5, 4.3.3, 4.3.4, 4.3.6				
<b>Part No.</b>	7018	<b>Part No. Revision</b>	E				
<b>Part Description</b>	Contractor FBH 3D Standard Non-Belted UniFit TB Legs MB Chest						
<b>Test Request No.</b>	PC-2301	<b>Date Complete</b>	7/27/2021				


### Test Summary (Continued)

Test Specification	Test Criteria	Test Result	Pass/Fail	
ANSI Z359.11-2021 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact $\geq$ 3,600 Lbf or 72" Free Fall	72" Free fall 3841.1 Lbf	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Remain Suspended for $\geq$ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Angle at Rest $\leq$ 30°	1.6°	Pass
	Dynamic Performance Dorsal D-ring (Head First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
ANSI Z359.11-2021 4.3.6	Fall Arrest Indicator Test (Dorsal D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
ANSI Z359.11-2021 4.3.6	Fall Arrest Indicator Test (Dorsal D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
ANSI Z359.11-2021 4.3.6	Fall Arrest Indicator Test (Dorsal D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass

### Conclusion

Based upon the samples provided to the Lab:  
 FallTech P/N 7018 Rev. E meets the requirements of ANSI Z359.11-2021

### Report Signatories and Approval

Lab Quality Manager		Date	8/4/2021
Witnessed by	Not Required	Date	N/A