

FallTech 7019BX Contractor 4D Cross-over Climbing Harness

Specification Sheet | SKU 7019BX | FallTech Body Wear

Features

- Plated alloy steel mating buckle torso adjusters deliver economical fit
- Includes single lanyard parking keeper.
- Plated alloy steel dorsal, hip, and sternal D-rings with mating buckle chest and leg closures
- Complies with ANSI Z359.11-2021



Technical Specifications

Product Type	Non-Belted Full Body Harness
D-Rings	4 D-Rings: Dorsal, Hip, Sternal
Adjustment	Mating Buckle Leg Adjustment
Webbing	Polyester; 5,000 lb min. static strength
D-Ring Hardware	Plated alloy steel; 5,000 lb min. static strength
Buckles and Adjusters	Plated alloy steel; 3,372 lb min. static strength
Static Strength	3,600 lb min.
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 425 lb max.
Standards	ANSI Z359.11-2021; OSHA 1926.502 and 1910.140; CSA Z259.10-2018
Available Configurations	7019B (UniFit (S, M, L)), 7019BX/2X (XL/2X)
Warranty	FallTech 2-Year Manufacturer Warranty

Fall Protection Distributors, LLC | standingseamroofanchor.com | 863-703-4522 | Distributor spec sheet compiled from FallTech published data.