

# FallTech 7021BFD Journeyman Flex Aluminum 2D Climbing Harness

Specification Sheet | SKU 7021BFD | FallTech Body Wear

## Features

- Exclusive aluminum camlock torso adjusters provide simple and secure upper-body fit that holds through the shift.
- The lightweight forged aluminum alloy dorsal D-ring cuts harness weight while the steel sternal D-ring handles climbing connections.
- The integral padded shoulder yoke and hip-to-seat leg pads provide advanced breathable user comfort.
- The proprietary dorsal attachment sleeve supports effortless addition of personal SRLs without extra adapters.
- Tongue buckle legs are uniquely equipped with 9 grommets adjustment positions for a wider range of fit.
- A fully adjustable suspension trauma relief system ships with the harness for post-fall suspension safety.



## Technical Specifications

|                          |                                                                                     |
|--------------------------|-------------------------------------------------------------------------------------|
| Type                     | Non-Belted Climbing Full Body Harness                                               |
| SKU                      | 7021BFD                                                                             |
| Family                   | Journeyman Flex Aluminum                                                            |
| D-Rings                  | 2 (Dorsal, Sternal)                                                                 |
| Closures                 | Tongue Buckle Legs and Quick-connect Chest                                          |
| Webbing                  | Polyester; 5,000 lb min. static strength                                            |
| D-Ring Hardware          | Aluminum alloy and plated alloy steel; 5,000 lb min. static strength                |
| Buckles and Adjusters    | Aluminum alloy and plated alloy steel; 3,372 lb min. static strength                |
| Static Strength          | 3,600 lb min.                                                                       |
| ANSI User Capacity       | 130 to 310 lb max.                                                                  |
| OSHA User Capacity       | 130 to 425 lb max.                                                                  |
| Standards                | OSHA 1926.502 and 1910.66; CSA Z259.10-2018                                         |
| Available Configurations | 7021BFDS (Small), 7021BFDXL (XL), 7021BFD2X (2X), 7021BFD3X (3X)                    |
| Warranty                 | FallTech 2-year manufacturer warranty, honored through Fall Protection Distributors |