

Declaration of Conformity

In Accordance with ANSI/ISEA 125-2014 and ANSI/ASSP Z359.7-2019



Alexander Andrew, Inc. 1306 S. Alameda St Compton, CA 90221 (800) 719-4619

Declaration #

B0608195

Declaration Date

6/8/2023

Tested Item #

7023B

Journeyman Flex Standard Non-belted FBH UniFit
Alum 3D TB Legs/QC Chest, w/ Trauma Pack

Additional Items Conforming Under this Declaration:

7021B	7021BCS2X	7023B2X	7023BS/M
7021B2X	7021BCSXL	7023B3X	7023BXL
7021BCS	7021BXL	7023BL/X	

Alexander Andrew, Inc. declares that the product(s) listed above is in conformity with the requirements of the following product standard(s):

ANSI Z359.11-2021

Conformity Assessment Method in accordance with ANSI/ISEA 125-2014

Level 1

Level 2

X

Level 3

Level 1: FallTech Lab
Outside the Scope of
ISO/IEC Standard 17025:2005

Level 2: FallTech Lab
Within the Scope of
ISO/IEC Standard 17025:2005

Level 3: Independent 3rd Party Lab
accredited to
ISO/IEC Standard 17025:2005

Supporting
Documentation

PC-2853

Authorized Signature

Name

Zachary Winters

Title

Engineering Manager

Date

6/8/2023



International Accreditation Service, Inc
3060 Saturn St, Ste 100
Brea, CA 92821 +1 562-364-8201

FallTech Lab - TL-594
ISO/IEC 17025:2017

Alexander Andrew Inc dba FallTech

FallTech Test Report

Test Report No.	PC-2853	Rpt. Date	6/7/2023	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Zachary Winters	Test Specification(s)	ANSI Z359.11-2021: 4.3.3, 4.3.4, 4.3.5, 4.3.6				
Part No.	7023B	Part No. Revision	F				
Part Description	Journeyman Flex Standard Non-belted FBH UniFit Alum 3D TB Legs/QC Chest						
Test Request No.	PC-2853	Date Complete	6/7/2023				
Test Operator(s)	Yesbet Sierra / Jay Sponholz						

Material/Sample Identification

Sample ID	Description
6882782	Journeyman Flex Standard Non-belted FBH UniFit Alum 3D TB Legs/QC Chest
6882783	Journeyman Flex Standard Non-belted FBH UniFit Alum 3D TB Legs/QC Chest
6882794	Journeyman Flex Standard Non-belted FBH UniFit Alum 3D TB Legs/QC Chest
6882792	Journeyman Flex Standard Non-belted FBH UniFit Alum 3D TB Legs/QC Chest
3882795	Journeyman Flex Standard Non-belted FBH UniFit Alum 3D TB Legs/QC Chest
6882798	Journeyman Flex Standard Non-belted FBH UniFit Alum 3D TB Legs/QC Chest
6882790	Journeyman Flex Standard Non-belted FBH UniFit Alum 3D TB Legs/QC Chest
6882786	Journeyman Flex Standard Non-belted FBH UniFit Alum 3D TB Legs/QC Chest
6882787	Journeyman Flex Standard Non-belted FBH UniFit Alum 3D TB Legs/QC Chest
6882740	Journeyman Flex Standard Non-belted FBH UniFit Alum 3D TB Legs/QC Chest
6882744	Journeyman Flex Standard Non-belted FBH UniFit Alum 3D TB Legs/QC Chest
6743200	Journeyman Flex Standard Non-belted FBH UniFit Alum 3D TB Legs/QC Chest
6882795	Journeyman Flex Standard Non-belted FBH UniFit Alum 3D TB Legs/QC Chest
6882798	Journeyman Flex Standard Non-belted FBH UniFit Alum 3D TB Legs/QC Chest
6882792	Journeyman Flex Standard Non-belted FBH UniFit Alum 3D TB Legs/QC Chest

Test Summary

Test Specification	Test Criteria	Test Result	Pass/Fail	
ANSI Z359.11-2021 4.3.5	Static Strength (Dorsal D-ring)	3600 Lbf ≥ 1 Minute	3628.4 Lbf	Pass
	Hold Test Torso	Shall Not Release Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage ≤ 1"	0.21"	Pass
	Tear Distance (Buckle)	Shall Not Tear > 1"	Did Not Tear Through	Pass
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.5	Static Strength (Dorsal D-ring)	3600 Lbf ≥ 1 Minute	3640.3 Lbf	Pass
	Hold Test Torso	Shall Not Release Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage ≤ 1"	0.27"	Pass
	Tear Distance (Buckle)	Shall Not Tear > 1"	Did Not Tear Through	Pass
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.5	Static Strength (Dorsal D-ring)	3600 Lbf ≥ 1 Minute	3636.4 Lbf	Pass
	Hold Test Torso	Shall Not Release Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage ≤ 1"	0.18"	Pass
	Tear Distance (Buckle)	Shall Not Tear > 1"	Did Not Tear Through	Pass
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear	Pass

FallTech Test Report

Test Report No.	PC-2853	Rpt. Date	6/7/2023	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Zachary Winters	Test Specification(s)	ANSI Z359.11-2021: 4.3.3, 4.3.4, 4.3.5, 4.3.6				
Part No.	7023B	Part No. Revision	F				
Part Description	Journeyman Flex Standard Non-belted FBH UniFit Alum 3D TB Legs/QC Chest						
Test Request No.	PC-2853	Date Complete	6/7/2023				

Test Summary Continued

Test Specification	Test Criteria	Test Result	Pass/Fail	
ANSI Z359.11-2021 4.3.5	Static Strength (Side D-rings)	3600 Lbf \geq 1 Minute	3668.9 Lbf	Pass
	Hold Test Torso	Shall Not Release Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage \leq 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear $>$ 1"	Did Not Tear Through	Pass
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.5	Static Strength (Side D-rings)	3600 Lbf \geq 1 Minute	3647.1 Lbf	Pass
	Hold Test Torso	Shall Not Release Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage \leq 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear $>$ 1"	Did Not Tear Through	Pass
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.5	Static Strength (Side D-rings)	3600 Lbf \geq 1 Minute	3655.3 Lbf	Pass
	Hold Test Torso	Shall Not Release Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage \leq 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear $>$ 1"	Did Not Tear Through	Pass
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load \geq 3600 Lbf	4265.4 Lbf	Pass
	Fall Arrest	Shall Not Release Torso	Did Not Release	Pass
	Post Drop Angle	Angle at Rest \leq 30°	2.2°	Pass
	Impact Indicator	One Indicator Shall Deploy	Permanently Deployed	Pass
	Harness Stretch	Shall Not Exceed 18"	11.5"	Pass
ANSI Z359.11-2021 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load \geq 3600 Lbf	4572.2 Lbf	Pass
	Fall Arrest	Shall Not Release Torso	Did Not Release	Pass
	Post Drop Angle	Angle at Rest \leq 30°	2.6°	Pass
	Impact Indicator	One Indicator Shall Deploy	Permanently Deployed	Pass
	Harness Stretch	Shall Not Exceed 18"	11.0"	Pass
ANSI Z359.11-2021 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load \geq 3600 Lbf	4462.8 Lbf	Pass
	Fall Arrest	Shall Not Release Torso	Did Not Release	Pass
	Post Drop Angle	Angle at Rest \leq 30°	3.9°	Pass
	Impact Indicator	One Indicator Shall Deploy	Permanently Deployed	Pass
	Harness Stretch	Shall Not Exceed 18"	10.2"	Pass

FallTech Test Report

Test Report No.	PC-2853	Rpt. Date	6/7/2023	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Zachary Winters	Test Specification(s)	ANSI Z359.11-2021: 4.3.3, 4.3.4, 4.3.5, 4.3.6				
Part No.	7023B	Part No. Revision	F				
Part Description	Journeyman Flex Standard Non-belted FBH UniFit Alum 3D TB Legs/QC Chest						
Test Request No.	PC-2853	Date Complete	6/7/2023				

Test Summary Continued

Test Specification	Test Criteria	Test Result	Pass/Fail	
ANSI Z359.11-2021 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact \geq 3,600 Lbf or 72" Free Fall	72" Free fall 3172.9 Lbf	Pass
	Fall Arrest	Shall Not Release Torso	Did Not Release	Pass
	Post Drop Angle	Angle at Rest \leq 30°	29.0°	Pass
	Impact Indicator	One Indicator Shall Deploy	Permanently Deployed	Pass
ANSI Z359.11-2021 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact \geq 3,600 Lbf or 72" Free Fall	72" Free fall 3111.7 Lbf	Pass
	Fall Arrest	Shall Not Release Torso	Did Not Release	Pass
	Post Drop Angle	Angle at Rest \leq 30°	26.9°	Pass
	Impact Indicator	One Indicator Shall Deploy	Permanently Deployed	Pass
ANSI Z359.11-2021 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact \geq 3,600 Lbf or 72" Free Fall	72" Free fall 3287.3 Lbf	Pass
	Fall Arrest	Shall Not Release Torso	Did Not Release	Pass
	Post Drop Angle	Angle at Rest \leq 30°	10.5°	Pass
	Impact Indicator	One Indicator Shall Deploy	Permanently Deployed	Pass
ANSI Z359.11-2021 4.3.6	Fall Arrest Indicator Test (Doral D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
ANSI Z359.11-2021 4.3.6	Fall Arrest Indicator Test (Doral D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
ANSI Z359.11-2021 4.3.6	Fall Arrest Indicator Test (Doral D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass

Conclusion

Based upon the samples provided to the Lab:
 FallTech P/N 7023B Rev. F meets the requirements of ANSI Z359.11-2021

Report Signatories and Approval

Lab Quality Manager		Date	6/7/2023
----------------------------	---	-------------	----------