

FallTech 7023X Journeyman Flex Steel 3D Harness, TB Legs

Specification Sheet | SKU 7023X | FallTech

Features

- Features integral padded shoulder yoke and hip-to-seat leg pads to provide advanced breathable user comfort.
- Proprietary dorsal attachment sleeve supports effortless addition of personal SRLs.
- Plated alloy steel low-profile spring tension roller torso adjusters provide simple upper-body adjustment.
- Dorsal and hip D-rings, quick connect chest, and tongue buckle leg closures are all durably plated alloy steel.
- Tongue buckle legs are uniquely equipped with 9 grommeted adjustment positions for a wider range of fit.
- Includes fully adjustable suspension trauma relief system.



Technical Specifications

Type	Non-Belted Full Body Harness
SKU	7023X
Family	Journeyman Flex Steel
D-Rings	3 (Dorsal and Hip)
Closures	Tongue Buckle Legs and Quick-connect Chest
Webbing	Polyester
Static Strength	3,600 lb min.
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 425 lb max.
Standards	ANSI Z359.11-2021; OSHA 1926.502 and 1910.140; CSA Z259.10-2018
Available Configurations	7023 (UniFit (S, M, L)), 7023XL (XL), 70232X (2X), 70233X (3X), 70234X (4X)
Warranty	FallTech 2-year manufacturer warranty, honored through Fall Protection Distributors

Fall Protection Distributors, LLC | standingseamroofanchor.com | 863-703-4522 | Distributor spec sheet compiled from FallTech published data.