

FallTech 7035B Journeyman Flex Aluminum 3D Belted Harness

Specification Sheet | SKU 7035B | FallTech

Features

- Features integral padded shoulder yoke, hip-to-seat leg, and 6" waist support positioning pads to provide advanced breathable user comfort.
- Proprietary dorsal attachment sleeve supports effortless addition of personal SRLs.
- Exclusive aluminum camlock torso adjusters provide simple and secure upper-body fit.
- Features lightweight forged aluminum alloy dorsal and hip D-rings.
- Tongue buckle legs are uniquely equipped with 9 grommeted adjustment positions for a wider range of fit.
- Quick-connect chest buckle features visual indicator showing positive connection.



Technical Specifications

Type	Belted Full Body Harness
SKU	7035B
Family	Journeyman Flex Aluminum
D-Rings	3 (Dorsal and Hip)
Closures	Tongue Buckle Legs and Quick-connect Chest
Webbing	Polyester
Static Strength	3,600 lb min.
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 425 lb max.
Standards	ANSI Z359.11-2021; OSHA 1926.502 and 1910.140; CSA Z259.10-2018
Available Configurations	7035BS (Small), 7035BM (Medium), 7035BL (Large), 7035BXL (XL), 7035B2X (2X), 7035B3X (3X), 7035B4X (4X)
Warranty	FallTech 2-year manufacturer warranty, honored through Fall Protection Distributors

Fall Protection Distributors, LLC | standingseamroofanchor.com | 863-703-4522 | Distributor spec sheet compiled from FallTech published data.