

FallTech 7036AX WeldTech 1D Standard Kevlar Harness, TB Legs

Specification Sheet | SKU 7036AX | FallTech Body Wear

Features

- Features Kevlar® webbing throughout shoulders, torso, and legs
- Kevlar® webbing delivers the highest level of burn and spatter resistance common in hot-work welding applications.
- Uniquely grommeted Kevlar® leg straps feature 9 adjustment positions for an expanded range of fit
- Friction roller torso adjusters provide simple upper-body adjustment
- D-ring, quick connect chest, and tongue buckle leg closures are all durably finished with plated alloy steel construction
- Quick-connect buckle features visual indicators showing positive connection
- Tongue buckle legs are uniquely equipped with 9 grommeted adjustment positions for a wider range of fit



Technical Specifications

Product Type	Non-Belted Full Body Harness
D-Rings	1 D-Ring: Dorsal
Adjustment	Tongue Buckle Leg Adjustment
Webbing	Kevlar®; 5,000 lb min. static strength
D-Ring Hardware	Plated alloy steel; 5,000 lb min. static strength
Buckles and Adjusters	Plated alloy steel; 3,372 lb min. static strength
Static Strength	3,600 lb min.
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 425 lb max.
Standards	ANSI Z359.11-2021; OSHA 1926.502 and 1910.140; CSA Z259.10-2018
Available Configurations	7036A (UniFit (S, M, L)), 7036AXL (XL), 7036A2X (2X)
Warranty	FallTech 2-Year Manufacturer Warranty

Fall Protection Distributors, LLC | standingseamroofanchor.com | 863-703-4522 | Distributor spec sheet compiled from FallTech published data.