

FallTech 7039X WeldTech 3D Standard Non-belted Harness

Specification Sheet | SKU 7039X | FallTech Body Wear

Features

- Features Nomex® webbing with Kevlar® fiber core throughout shoulders, torso and legs for pliable user-comfort
- Nomex®/Kevlar® blend webbing delivers excellent burn and spatter resistance common in hot-work welding applications.
- Friction roller torso adjusters provide simple upper-body adjustment
- D-rings, mating buckle chest, and quick-connect leg closures are all durably finished with plated alloy steel construction
- Quick-connect buckles feature visual indicators showing positive connection
- Complies with ANSI Z359.11-2021



Technical Specifications

| | |
|---------------------------------|---|
| Product Type | Non-Belted Full Body Harness |
| D-Rings | 3 D-Rings: Dorsal, Hip |
| Adjustment | Quick-Connect Leg Adjustment |
| Webbing | Nomex®/Kevlar®; 5,000 lb min. static strength |
| D-Ring Hardware | Plated alloy steel; 5,000 lb min. static strength |
| Buckles and Adjusters | Plated alloy steel; 3,372 lb min. static strength |
| Static Strength | 3,600 lb min. |
| ANSI User Capacity | 130 to 310 lb max. |
| OSHA User Capacity | 130 to 425 lb max. |
| Standards | ANSI Z359.11-2021; OSHA 1926.502 and 1910.140; CSA Z259.10-2018 |
| Available Configurations | 7039 (UniFit (S, M, L)), 7039XL (XL) |
| Warranty | FallTech 2-Year Manufacturer Warranty |

Fall Protection Distributors, LLC | standingseamroofanchor.com | 863-703-4522 | Distributor spec sheet compiled from FallTech published data.