

FallTech 70403D FT-Weld 3D Harness, Quick Connect Buckle Legs

Specification Sheet | SKU 70403D | FallTech

Features

- All Kevlar® webbing, delivering the highest level of burn and spatter resistance common in hot-work welding applications.
- New ergonomic lateral leg straps and construction greatly improve comfort and mobility. No more disconnecting leg straps when not in use.
- New ArrowGrip® dorsal D-ring plate minimizes slippage for maximum comfort and minimal adjustment throughout the day.
- Minimalistic back pad design for maximum comfort.
- Updated SRL connection point allows for fast, hassle-free attachment of all types of single and twin SRLs.
- Durable lanyard keeper design improves versatility and reusability while maintaining ANSI compliance.



Technical Specifications

Type	Non-Belted Full Body Harness
SKU	70403D
Family	FT-Weld
D-Rings	3 (Dorsal and Hip)
Closures	Quick-connect Legs and Chest
Webbing	Kevlar
Static Strength	3,600 lb min.
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 425 lb max.
Standards	ANSI Z359.11-2014; OSHA 1926.502 and 1910.140
Available Configurations	70403DXS (XS), 70403DSM (S/M), 70403DLXL (L/XL), 70403D2X3X (2X/3X)
Warranty	FallTech 2-year manufacturer warranty, honored through Fall Protection Distributors

Fall Protection Distributors, LLC | standingseamroofanchor.com | 863-703-4522 | Distributor spec sheet compiled from FallTech published data.