

# FallTech 7047FQC Arc Flash Harness 3D QC, Suspension Trauma Pack

Specification Sheet | SKU 7047FQC | FallTech Body Wear

## Features

- Features premium dielectric overmolded alloy steel dorsal D-ring, mating buckle leg, chest, and torso adjusters
- Arc resistant Nomex® webbing with Kevlar® fiber core throughout shoulders, torso and legs.
- Includes paired lanyard parking keepers and Nomex® label cover
- Meets ASTM F887 Standards
- Complies with ANSI Z359.11-2014



## Technical Specifications

<b>Product Type</b>	Non-Belted Full Body Harness
<b>D-Rings</b>	1 D-Ring: Dorsal
<b>Adjustment</b>	Mating Buckle Leg Adjustment
<b>Webbing</b>	Nomex®/Kevlar®; 5,000 lb min. static strength
<b>D-Ring Hardware</b>	Overmolded Alloy Steel; 5,000 lb min. static strength
<b>Buckles and Adjusters</b>	Overmolded alloy steel; 3,372 lb min. static strength
<b>Static Strength</b>	3,600 lb min.
<b>ANSI User Capacity</b>	130 to 310 lb max.
<b>OSHA User Capacity</b>	130 to 425 lb max.
<b>Standards</b>	ANSI Z359.11-2014; OSHA 1926.502 and 1910.140; ASTM F887
<b>Available Configurations</b>	7047FQCS (Small), 7047FQCM (Medium), 7047FQCL (Large), 7047FQCXL (XL), 7047FQC2X (2X), 7047FQC3X (3X)
<b>Warranty</b>	FallTech 2-Year Manufacturer Warranty

Fall Protection Distributors, LLC | standingseamroofanchor.com | 863-703-4522 | Distributor spec sheet compiled from FallTech published data.