

FallTech 7047X Arc Flash Nomex 1D Standard Non-belted Harness

Specification Sheet | SKU 7047X | FallTech Body Wear

Features

- Features premium dielectric overmolded alloy steel dorsal D-ring, mating buckle leg, chest, and torso adjusters
- Arc resistant Nomex® webbing with Kevlar® fiber core throughout shoulders, torso and legs.
- Includes paired lanyard parking keepers and Nomex® label cover
- Meets ASTM F887 Standards
- Complies with ANSI Z359.11-2014



Technical Specifications

Product Type	Non-Belted Full Body Harness
D-Rings	1 D-Ring: Dorsal
Adjustment	Mating Buckle Leg Adjustment
Webbing	Nomex®/Kevlar®; 5,000 lb min. static strength
D-Ring Hardware	Overmolded Alloy Steel; 5,000 lb min. static strength
Buckles and Adjusters	Overmolded alloy steel; 3,372 lb min. static strength
Static Strength	3,600 lb min.
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 425 lb max.
Standards	ANSI Z359.11-2014; OSHA 1926.502 and 1910.140; ASTM F887
Available Configurations	7047 (UniFit), 7047XL (XL), 70472X (2X), 70473X (3X)
Warranty	FallTech 2-Year Manufacturer Warranty

Fall Protection Distributors, LLC | standingseamroofanchor.com | 863-703-4522 | Distributor spec sheet compiled from FallTech published data.