

FallTech 7049QCX Arc Flash Nylon Harness 1D QC Dielectric

Specification Sheet | SKU 7049QCX | FallTech Body Wear

Features

- Features premium dielectric overmolded alloy steel dorsal D-ring, mating buckle leg, chest, and torso adjusters
- Nylon webbing throughout shoulders, torso, and legs provides economical level of arc flash resistance.
- Includes paired lanyard parking keepers and Nomex® label cover
- Meets ASTM F887 Standards
- Complies with ANSI Z359.11-2014



Technical Specifications

Product Type	Non-Belted Full Body Harness
D-Rings	1 D-Ring: Dorsal
Adjustment	Mating Buckle Leg Adjustment
Webbing	Nylon; 5,000 lb min. static strength
D-Ring Hardware	Overmolded Alloy Steel; 5,000 lb min. static strength
Buckles and Adjusters	Overmolded alloy steel; 3,372 lb min. static strength
Static Strength	3,600 lb min.
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 425 lb max.
Standards	ANSI Z359.11-2014; ASTM F887; OSHA 1926.502 and 1910.66
Available Configurations	7049QC (UniFit), 7049QCXL (XL), 7049QC2X (2X)
Warranty	FallTech 2-Year Manufacturer Warranty

Fall Protection Distributors, LLC | standingseamroofanchor.com | 863-703-4522 | Distributor spec sheet compiled from FallTech published data.