

FallTech 7051BFD Arc Flash Nylon 2D Climbing Non-belted Harness

Specification Sheet | SKU 7051BFD | FallTech

Features

- Features economical dielectric leather insulated alloy steel quick-connect chest buckle, mating buckle leg buckles and torso adjusters.
- Nylon webbing throughout shoulders, torso, and legs provides economical level of arc flash resistance.
- Quick-connect buckles feature indicators for positive visual engagement.
- Includes paired lanyard parking keepers and Nomex® label cover.
- Meets ASTM F887 Standards.
- Complies with ANSI Z359.11-2021.



Technical Specifications

Type	Non-Belted Full Body Harness
SKU	7051BFD
Family	Arc Flash
D-Rings	2 (Dorsal and Sternal)
Closures	Quick-connect Chest and Mating Buckle Legs
Webbing	Nylon
Static Strength	3,600 lb min.
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 425 lb max.
Standards	ANSI Z359.11-2021; OSHA 1926.502 and 1910.140; ASTM F887-20
Available Configurations	7051BFDXS (XS), 7051BFDS (S), 7051BFDM (M), 7051BFDL (L), 7051BFDXL (XL), 7051BFD2X (2X), 7051BFD3X (3X)
Warranty	FallTech 2-year manufacturer warranty, honored through Fall Protection Distributors

Fall Protection Distributors, LLC | standingseamroofanchor.com | 863-703-4522 | Distributor spec sheet compiled from FallTech published data.