

FallTech 7054FD Arc Flash Nylon 2D Climbing Harness

Specification Sheet | SKU 7054FD | FallTech Body Wear

Features

- New wishbone shaped shoulder yoke reduces neck irritation and improves comfort
- Features premium dielectric overmolded alloy steel dorsal and sternal D-rings, quick-connect buckle leg, chest, belt and torso adjusters
- Nylon webbing throughout shoulders, torso, and legs provides economical level of arc flash resistance.
- Shoulder yoke and sub-pelvic leg pads feature ripstop and quilted Nomex® fabrics for advanced Arc Flash protection
- Quick-connect buckles feature indicators for positive visual engagement
- Includes paired lanyard parking keepers and Nomex® label cover
- Meets ASTM F887 Standards



Technical Specifications

Product Type	Non-Belted Full Body Harness
D-Rings	2 D-Rings: Dorsal, Sternal
Adjustment	Quick-Connect Leg Adjustment
Webbing	Nylon; 5,000 lb min. static strength
D-Ring Hardware	Overmolded alloy steel; 5,000 lb min. static strength
Buckles and Adjusters	Overmolded alloy steel; 3,372 lb min. static strength
Static Strength	3,600 lb min.
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 425 lb max.
Standards	ANSI Z359.11-2014; ASTM F887; OSHA 1926.502 and 1910.66
Available Configurations	7054FDXS (XS), 7054FDS (Small), 7054FDM (Medium), 7054FDL (Large), 7054FDXL (XL), 7054FD2X (2X), 7054FD3X (3X)
Warranty	FallTech 2-Year Manufacturer Warranty

Fall Protection Distributors, LLC | standingseamroofanchor.com | 863-703-4522 | Distributor spec sheet compiled from FallTech published data.