

FallTech 7078C Tradesman Pro 3D Belted Harness, TB Legs

Specification Sheet | SKU 7078C | FallTech

Features

- Features all-black plated alloy steel hardware for refined, low profile look.
- V-slot locking D-ring plate minimizes slippage for maximum comfort and minimal adjustment throughout the day.
- Dorsal attachment tunnel allows for fast, hassle-free connection of single or twin SRL-Ps and keeps them optimally positioned on the back reducing fatigue.
- Features integral tri-layer padded shoulder yoke to provide breathable user comfort.
- Heavy duty waist pads provides support without folding for improved comfort.
- Plated alloy steel low-profile spring tension roller torso adjusters provide simple upper-body adjustment.



Technical Specifications

Type	Belted Full Body Harness
SKU	7078C
Family	Tradesman Pro
D-Rings	3 (Dorsal and Hip)
Closures	Tongue Buckle Legs and Quick-connect Chest
Webbing	Polyester
Static Strength	3,600 lb min.
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 425 lb max.
Standards	ANSI Z359.11-2021; CSA Z259.10-2018; OSHA 1926.502 and 1910.66
Available Configurations	7078CXS (XS), 7078CSM (S/M), 7078CLX (L/XL), 7078C2X3X (2XL/3XL)
Warranty	FallTech 2-year manufacturer warranty, honored through Fall Protection Distributors

Fall Protection Distributors, LLC | standingseamroofanchor.com | 863-703-4522 | Distributor spec sheet compiled from FallTech published data.