

FallTech 7079B Tradesman Plus 1D Construction Belted Harness

Specification Sheet | SKU 7079B | FallTech Body Wear

Features

- Features integral tri-layer padded shoulder yoke and 6" waist support positioning pad to provide breathable user comfort
- Proprietary dorsal attachment sleeve supports effortless addition of personal SRLs.
- Plated alloy steel low-profile spring tension roller torso adjusters provide simple upper-body adjustment
- Dorsal D-ring, quick connect chest, and tongue buckle leg closures are all durably plated alloy steel
- Quick-connect buckle features visual indicators showing positive connection
- Tongue buckle legs are uniquely equipped with 9 grommeted adjustment positions for a wider range of fit
- Complies with ANSI Z359.11-2014



Technical Specifications

Product Type	Belted Full Body Harness
D-Rings	1 D-Ring: Dorsal
Adjustment	Tongue Buckle Leg Adjustment
Webbing	Polyester; 5,000 lb min. static strength
D-Ring Hardware	Plated alloy steel; 5,000 lb min. static strength
Buckles and Adjusters	Plated alloy steel; 3,372 lb min. static strength
Static Strength	3,600 lb min.
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 425 lb max.
Standards	ANSI Z359.11-2014; OSHA 1926.502 and 1910.140; CSA Z259.10-2018
Available Configurations	7079BSM (S/M), 7079BLX (L/XL), 7079B2X (2X)
Warranty	FallTech 2-Year Manufacturer Warranty

Fall Protection Distributors, LLC | standingseamroofanchor.com | 863-703-4522 | Distributor spec sheet compiled from FallTech published data.