

FALLTECH®



ARC-FLASH ⚠

FT-R®

SRL-R

Premium SRL-R

Built on the premium performance of the FT-R platform, the FT-R Arc Flash SRL-R delivers confident control in the toughest arc-risk environments. This latest edition to FallTech's premium FT-series products combines smooth lifeline movement, intuitive retrieval operation, and proven arc-rated protection—so you can enter, work, and exit with complete trust in your gear.



01 ARC FLASH PROTECTION

ASTM F887-rated with a tough Technora® lifeline built to stand up to the blistering heat and crushing power of arc flash hazards when performance matters most.



02 DUAL-MODE FUNCTIONALITY

Simplified controls make switching from fall arrest to rescue fast and direct—just pull the plunger pin and shift the crank. No tools. No delays.



03 OPTIMIZED MOVEMENT

A refined internal system cuts down nuisance lockups, delivering smooth, natural motion every step.



04 LIGHTWEIGHT & ROBUST DESIGN

Engineered to be lighter than leading units without giving up an ounce of strength.



05 EASY INSTALLATION

Fast, secure mounting to tripods or modular davits ensures reliable performance in the tightest spaces.



06 PROTECTED LABELS

UV- and scratch-resistant labels help keep key information legible—and units compliant—in tough work environments.



When arc flash risk is part of the job, there is no margin for failure. The FT-R Arc Flash SRL-R meets strict OSHA, ANSI, and ASTM standards, delivering proven fall protection and trusted arc flash resistance workers can rely on. The FT-R Arc Flash SRL-R is Class 1 rated for anchoring at, above, or up to 5 feet below D-ring on worksites without edge exposure.



RELEVANT STANDARDS

- ANSI Z359.14-2021
- ASTM F887-20
- OSHA 1926.502

MATERIAL SPECIFICATIONS

- **Housing:** Glass-Reinforced Nylon
- **Lifeline:** ¼" Technora® Rope (3,600 lb. min. strength)
- **Lifeline Connector:** Overmolded/Plated Alloy Steel (5,000 lb. min. strength with 3,600 lb. min. gate strength)
- **Anchorage Connector:** Variable (5,000 lb. min. strength with 3,600 lb. min. gate strength)

PERFORMANCE SPECIFICATIONS

- **Max Arrest Force:** 1,800 lbs.
- **Average Arrest Force:** 1,575 lbs. or less
- **Max Arrest Distance:** 42 in. or less
- **Static Strength:** 3,600 lbs. (min.)
- **Max User Capacity (ANSI):** 310 lbs.
- **Max User Capacity (OSHA):** 420 lbs.

Part Number	Description
721560RT	FT-R Arc Flash SRL-R (60') w/ Steel Snap Hook
721560RTD1	FT-R Arc Flash SRL-R (60') w/ Dielectric Snap Hook
7508TB	8' Tripod Kit w/ FT-R Arc Flash SRL-R (721560RT) + Storage Bags
7509TB	8' Tripod Kit w/ FT-R Arc Flash SRL-R (721560RT) and Personnel Winch (7297T) + Storage Bags

Find Our Full Selection of Fall Protection Products at FallTech.com



©2025 Alexander Andrew, Inc.
1306 S. Alameda St.
Compton, CA 90221-4803

Tel / 323.752.0066

Fax / 323.752.5613

Tools shown not included.

Product description and specifications
herein may change without notice.

U.S. and International Patents Pending.

