

FallTech CTR Class 2 Leading Edge Cable SRL, 20 to 60 ft

Specification Sheet | SKU 7237LE | FallTech

Features

- Tested per ANSI Z359.14-2021 for foot-level tie-off and lifeline loading over an edge, the failure mode that destroys non-LE devices.
- The leading edge cable is a full size heavier than the Class 1 CTR, maintaining 3,600 lb minimum static strength through edge contact.
- A leg-end energy absorber manages the higher arrest loads of foot-level falls and keeps forces on the worker at or under 1,350 lb average.
- The same jobsite-proof housing and steel-reinforced carry handle as the Class 1, built for daily staging and transport.
- The internal mechanism reduces nuisance lockups at natural working speeds, so the cable follows you across the deck instead of fighting you.
- The swivel leg-end connection prevents lifeline twist during horizontal movement along the edge.



Technical Specifications

Type	Class 2 Leading Edge Self-Retracting Lifeline, Cable
SKU	7237LE
Lifeline	7/32" galvanized steel wire rope; 3,600 lb min. static strength
Housing	Glass-reinforced nylon with steel-reinforced carry handle
Energy Absorber	Integrated leg-end energy absorber, edge rated
Connector	Steel swivel snap hook; steel anchorage carabiner
Average Arrest Force	1,350 lb maximum
ANSI User Capacity	130 to 310 lb including clothing and tools
Standards	ANSI Z359.14-2021 Class 2; OSHA 1926.502 and 1910.66; CSA Z259.2.2-2017
Available Configurations	723720LE (20 ft), 723730LE (30 ft), 723760LE (60 ft)
Warranty	FallTech 2-year manufacturer warranty, honored through Fall Protection Distributors

Fall Protection Distributors, LLC | standingseamroofanchor.com | 863-703-4522 | Distributor spec sheet compiled from FallTech published data.