

# FallTech 7533 12 in Trailing Beam Clamp Anchor, Dual-Clamp

FallTech | Fall Protection Distributors, LLC

<b>SKU</b>	7533
<b>Type</b>	Trailing beam clamp anchor, dual-clamp adjustment
<b>Anchorage classification</b>	ANSI Z359.18-2017
<b>Strength</b>	5,000 lb (22.2 kN)
<b>Capacity (ANSI)</b>	One worker, 130 to 310 lb combined
<b>Capacity (OSHA)</b>	One worker, 130 to 425 lb combined
<b>Beam flange width range</b>	3.5 in to 12 in
<b>Beam flange thickness</b>	Up to 1 in
<b>Maximum flange-to-jaw gap</b>	1/2 in
<b>Mounting</b>	Trailing top flange or overhead bottom flange
<b>Beam type</b>	I-beam or H-beam; not open-ended (end stops required)
<b>Materials</b>	Steel beam clamp with swiveling D-ring
<b>Standards</b>	ANSI Z359.18-2017; OSHA 1926.502 and 1910
<b>Warranty</b>	FallTech 2-year limited warranty against defects in materials and workmanship

863-703-4522 | [standingseamroofanchor.com](http://standingseamroofanchor.com) | Read the FallTech manual before use.