

# FallTech 7535 12 in Stationary Vertical Beam Anchor

FallTech | Fall Protection Distributors, LLC

<b>SKU</b>	7535
<b>Type</b>	Stationary vertical beam anchor for fixed locations
<b>Anchorage classification</b>	ANSI Z359.18-2017; ANSI Z359.7
<b>Strength</b>	5,000 lb (22.2 kN)
<b>Capacity (ANSI)</b>	One worker, 130 to 310 lb combined (single-user PFAS)
<b>Capacity (OSHA)</b>	One worker, 130 to 425 lb combined
<b>Beam flange width range</b>	4.5 in to 12 in
<b>Beam flange thickness</b>	Up to 2 in
<b>Maximum flange-to-jaw gap</b>	1/2 in
<b>Mounting</b>	Horizontal or vertical I-beam or H-beam; fixed location
<b>Multi-user</b>	May anchor a compatible FallTech HLL for more than one user
<b>Materials</b>	Steel beam anchor with D-ring
<b>Standards</b>	ANSI Z359.18-2017; ANSI Z359.7; OSHA 1926.502 and 1910
<b>Warranty</b>	FallTech 2-year limited warranty against defects in materials and workmanship

863-703-4522 | [standingseamroofanchor.com](http://standingseamroofanchor.com) | Read the FallTech manual before use.