

# Premium Anchor

Reliable Support at Any Height

## The BeamLock™ is the most innovative, versatile, and premium FallTech® anchor yet.

This new anchor is built for secure, adjustable attachment to I- and H-beams with flanges ranging from 4 to 14 inches. Thanks to an intuitive push-button design, the BeamLock allows quick and easy attachment, detachment, and adjustment from any angle, streamlining the anchoring process.

The BeamLock is engineered for frictionless trailing movement, featuring replaceable short and long slider pads that eliminate metal-on-metal contact. Its 360-degree swivel D-ring minimizes binding, enhancing mobility while keeping you secure.

With scratch- and UV-resistant labeling, the BeamLock offers long-lasting visibility and compliance with safety standards. Whether for overhead or trailing applications, this innovative anchor gives you lasting support at height.

### The BeamLock will launch with the following part numbers:

Part Number	Description
7540A14	BeamLock Anchor w/ 2x Slider Pads + Screws
7542A	Short Replacement Slider Pads (2-Pk + Screws)
7542B	Long Replacement Slider Pads (2-Pk + Screws)



7540A14



7542A



7542B

### The BeamLock complies with the following standards:

- ANSI Z359.18-2017 Type A
- CSA Z259.15-2017 Type A
- OSHA 1926.502, 1910.140

### Below are performance specifications:

- Static Strength: 5,000 lb (min.)
- User Capacity: One user up to 310 lb (ANSI) or 425 lb (OSHA and CSA)