

# FallTech 7540A14 BeamLock Beam Anchor, 4 in to 14 in

FallTech | Fall Protection Distributors, LLC

<b>SKU</b>	7540A14
<b>Type</b>	BeamLock beam anchor, dual adjustment
<b>Anchorage classification</b>	ANSI Z359.18-2017 Type A
<b>Strength</b>	5,000 lb (22.2 kN)
<b>Capacity (ANSI)</b>	One worker, 130 to 310 lb combined
<b>Capacity (OSHA)</b>	One worker, 130 to 425 lb combined
<b>Beam flange width range</b>	4 in to 14 in
<b>Beam flange thickness</b>	Up to 1-1/4 in
<b>Maximum flange-to-jaw gap</b>	11/16 in
<b>Included</b>	Long and short wear-pad sets
<b>Mounting</b>	Trailing top flange or overhead bottom flange
<b>Materials</b>	Aluminum body, steel jaws, plated steel swiveling D-ring
<b>Standards</b>	ANSI Z359.18-2017; OSHA 1926.502 and 1910
<b>Warranty</b>	FallTech 2-year limited warranty against defects in materials and workmanship

863-703-4522 | [standingseamroofanchor.com](http://standingseamroofanchor.com) | Read the FallTech manual before use.