

# FallTech 100 ft 2-Person Polyester Rope Temporary HLL

Part Number(s): 770001 | Brand: FallTech | Product Specification Sheet

## Features

- Features 5/8" low-stretch hollow-core polyester rope with one braided and thimbled end-termination
- Includes plated steel line tensioner and 2 installation carabiners.
- Also includes 2 pass-through anchors and 2 connecting rings
- Meets OSHA 1926.502 and 1910.66 regulations



## Specifications

<b>Description</b>	100' Polyester hollow-core rope
<b>Static Strength</b>	5,000 lb min.
<b>OSHA User Capacity</b>	310 lb max. per user; 2 users max.
<b>Rope</b>	5/8" braided 12-strand hollow-core polyester; 5,000 lb min.
<b>Sling Anchors</b>	Polyester webbing with plated alloy steel D-rings; 5,000 lb min. static strength
<b>Carabiners</b>	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength
<b>Tensioner and Connecting Rings</b>	Plated alloy steel; 5,000 lb min. static strength
<b>Unit Weight</b>	24.38 lb
<b>Relevant Standards</b>	OSHA 1926.502 and 1910.66

Distributed by Fall Protection Distributors, LLC, an authorized FallTech dealer. [standingseamroofanchor.com](http://standingseamroofanchor.com) | 863-703-4522.  
Specifications from FallTech published product data. Always follow the FallTech instruction manual.