

## Lightweight Beam Trolley Anchor ////////////////////////////////////

The FallTech™ Beam Trolley is a lightweight mobile anchorage connector solution for use in Personal Fall Arrest Systems. Positioned anywhere along an overhead horizontal I-beam, the Beam Trolley will effortlessly follow the user and is ideally suited for use with SRLs in general industry applications.



7712 | Beam Trolley Anchor

### Material Specifications

<b>D-ring:</b>	Aluminum Alloy; 5,000 lbs Min Static Strength
<b>Crossbar:</b>	Aluminum Alloy

### Performance Specifications

<b>Static Strength:</b>	5,000 lbs
<b>Min Use Temperature:</b>	10° Fahrenheit
<b>ANSI Anchor Class:</b>	Type D
<b>ANSI User Capacity:</b>	310 lbs or less
<b>OSHA User Capacity:</b>	425 lbs or less

- Fits I-beams from 4" to 18" wide and up to 1¼" thick.
- Features aluminum crossbar, side plates and 360° swiveling D-ring.
- High density Nylacast wheels provide high continuous service temperature resistance and low moisture absorption rate.
- Stainless Steel wheel guards and fasteners plus sealed stainless steel wheel bearings.
- Features simple beam width adjustment with secondary locking detent pin.
- Weighs only 8½ lbs.

### Relevant Standards

<b>ANSI</b>	Z359.18-2017
<b>OSHA</b>	1926.502

Product descriptions and specifications herein may change without notice.