

FallTech 8026X Roughneck 5D Derrick Cross-over Belted Harness

Specification Sheet | SKU 8026X | FallTech Body Wear

Features

- Unique combination of five D-rings to address multiple user applications involved with derrick climbing and positioning
- Featured 4" wrap-around waist support positioning pad enhances user comfort and supports integrated tool belt.
- Friction roller torso adjusters provide simple upper-body adjustment
- D-rings, tongue buckle leg, and mating buckle chest closures are all durably finished with plated alloy steel construction
- Tongue buckle legs are uniquely equipped with 9 grommeted adjustment positions for a wider range of fit
- Meets OSHA 1926.502 and 1910.66 Regulations



Technical Specifications

Product Type	Belted Full Body Harness
D-Rings	5 D-Rings: Dorsal, Hip, Dorsal Extension, Restraint
Adjustment	Tongue Buckle Leg Adjustment
Webbing	Polyester; 5,000 lb min. static strength
D-Ring Hardware	Plated alloy steel; 5,000 lb min. static strength
Buckles and Adjusters	Plated alloy steel; 3,372 lb min. static strength
Static Strength	3,600 lb min.
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 425 lb max.
Standards	OSHA 1926.502 and 1910.140
Available Configurations	8026 (UniFit (S, M, L)), 8026X/2X (XL/2X)
Warranty	FallTech 2-Year Manufacturer Warranty

Fall Protection Distributors, LLC | standingseamroofanchor.com | 863-703-4522 | Distributor spec sheet compiled from FallTech published data.