

# Declaration of Conformity

In Accordance with ANSI/ISEA 125-2014 and ANSI/ASSP Z359.7-2019



Alexander Andrew, Inc. 1306 S. Alameda St Compton, CA 90221 (800) 719-4619

Declaration #

B0425186a

Declaration Date

6/14/2024

Tested Item #

8127BM

FT-One FBH 3D Construction Belted, Medium, TB  
Legs/QC Chest

Additional Items Conforming Under this Declaration:

8127BXS	8127BXL	8128BXS	8128BL	8128B3X	8048L
8127BS	8127B2X	8128BS	8128BXL	8048S	8048XL
8127BL	8127B3X	8128BM	8128B2X	8048M	80482X

Alexander Andrew, Inc. declares that the product(s) listed above is in conformity with the requirements of the following product standard(s):

ANSI Z359.11-2021

Conformity Assessment Method in accordance with ANSI/ISEA 125-2014

Level 1

Level 2

Level 3

Level 1: FallTech Lab  
Outside the Scope of  
ISO/IEC Standard 17025:2005

Level 2: FallTech Lab  
Within the Scope of  
ISO/IEC Standard 17025:2005

Level 3: Independent 3rd Party Lab  
accredited to  
ISO/IEC Standard 17025:2005

Supporting  
Documentation

PC-2822

Authorized Signature

Name

Zachary Winters

Title

Engineering Manager

Date

6/14/2024



International Accreditation Service, Inc  
3060 Saturn St, Ste 100  
Brea, CA 92821 +1 562-364-8201

FallTech Lab - TL-594  
ISO/IEC 17025:2017

Alexander Andrew Inc dba FallTech

### FallTech Test Report

<b>Test Report No.</b>	PC-2822	<b>Rpt. Date</b>	4/24/2023	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Zachary Winters	<b>Test Specification(s)</b>	ANSI Z359.11-2021: 4.3.3, 4.3.4, 4.3.5, 4.3.6				
<b>Part No.</b>	8127BM	<b>Part No. Revision</b>	C				
<b>Part Description</b>	FT-One FBH 3D Construction Belted, Medium, TB Legs / QC Chest						
<b>Test Request No.</b>	PC-2822	<b>Date Complete</b>	4/24/2023				
<b>Test Operator(s)</b>	Yesbet Sierra / Jay Sponholz						

### Material/Sample Identification

Sample ID	Description
6847077	FT-One FBH 3D Construction Belted, Medium, TB Legs / QC Chest
6847092	FT-One FBH 3D Construction Belted, Medium, TB Legs / QC Chest
6847088	FT-One FBH 3D Construction Belted, Medium, TB Legs / QC Chest
6847091	FT-One FBH 3D Construction Belted, Medium, TB Legs / QC Chest
6847090	FT-One FBH 3D Construction Belted, Medium, TB Legs / QC Chest
6847087	FT-One FBH 3D Construction Belted, Medium, TB Legs / QC Chest
6847093	FT-One FBH 3D Construction Belted, Medium, TB Legs / QC Chest
6847084	FT-One FBH 3D Construction Belted, Medium, TB Legs / QC Chest
6847089	FT-One FBH 3D Construction Belted, Medium, TB Legs / QC Chest
6847082	FT-One FBH 3D Construction Belted, Medium, TB Legs / QC Chest
6847080	FT-One FBH 3D Construction Belted, Medium, TB Legs / QC Chest
6847078	FT-One FBH 3D Construction Belted, Medium, TB Legs / QC Chest
6847090	FT-One FBH 3D Construction Belted, Medium, TB Legs / QC Chest
6847087	FT-One FBH 3D Construction Belted, Medium, TB Legs / QC Chest
6847091	FT-One FBH 3D Construction Belted, Medium, TB Legs / QC Chest

### Test Summary

Test Specification	Test Criteria	Test Result	Pass/Fail	
ANSI Z359.11-2021 4.3.5	Static Strength (Dorsal D-ring)	3600 Lbf $\geq$ 1 Minute	3625.9 Lbf	Pass
	Hold Test Torso	Shall Not Release Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.23"	Pass
	Tear Distance (Buckle)	Shall Not Tear > 1"	Did Not Tear Through	Pass
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.5	Static Strength (Dorsal D-ring)	3600 Lbf $\geq$ 1 Minute	3640.0 Lbf	Pass
	Hold Test Torso	Shall Not Release Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.13"	Pass
	Tear Distance (Buckle)	Shall Not Tear > 1"	Did Not Tear Through	Pass
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.5	Static Strength (Dorsal D-ring)	3600 Lbf $\geq$ 1 Minute	3704.8 Lbf	Pass
	Hold Test Torso	Shall Not Release Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.21"	Pass
	Tear Distance (Buckle)	Shall Not Tear > 1"	Did Not Tear Through	Pass
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear	Pass

### FallTech Test Report

<b>Test Report No.</b>	PC-2822	<b>Rpt. Date</b>	4/24/2023	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Zachary Winters	<b>Test Specification(s)</b>		ANSI Z359.11-2021: 4.3.3, 4.3.4, 4.3.5, 4.3.6			
<b>Part No.</b>	8127BM	<b>Part No. Revision</b>			C		
<b>Part Description</b>	FT-One FBH 3D Construction Belted, Medium, TB Legs / QC Chest						
<b>Test Request No.</b>	PC-2822	<b>Date Complete</b>			4/24/2023		

### Test Summary Continued

Test Specification	Test Criteria	Test Result	Pass/Fail	
ANSI Z359.11-2021 4.3.5	Static Strength (Side D-rings)	3600 Lbf $\geq$ 1 Minute	3635.8 Lbf	Pass
	Hold Test Torso	Shall Not Release Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear > 1"	Did Not Tear Through	Pass
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.5	Static Strength (Side D-rings)	3600 Lbf $\geq$ 1 Minute	3630.4 Lbf	Pass
	Hold Test Torso	Shall Not Release Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear > 1"	Did Not Tear Through	Pass
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.5	Static Strength (Side D-rings)	3600 Lbf $\geq$ 1 Minute	3650.1 Lbf	Pass
	Hold Test Torso	Shall Not Release Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear > 1"	Did Not Tear Through	Pass
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load $\geq$ 3600 Lbf	4322.3 Lbf	Pass
	Fall Arrest	Shall Not Release Torso	Did Not Release	Pass
	Post Drop Angle	Angle at Rest $\leq$ 30°	3.7°	Pass
	Impact Indicator	One Indicator Shall Deploy	Permanently Deployed	Pass
	Harness Stretch	Shall Not Exceed 18"	10.4"	Pass
ANSI Z359.11-2021 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load $\geq$ 3600 Lbf	4306.7 Lbf	Pass
	Fall Arrest	Shall Not Release Torso	Did Not Release	Pass
	Post Drop Angle	Angle at Rest $\leq$ 30°	3.3°	Pass
	Impact Indicator	One Indicator Shall Deploy	Permanently Deployed	Pass
	Harness Stretch	Shall Not Exceed 18"	10.3"	Pass
ANSI Z359.11-2021 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load $\geq$ 3600 Lbf	4224.0 Lbf	Pass
	Fall Arrest	Shall Not Release Torso	Did Not Release	Pass
	Post Drop Angle	Angle at Rest $\leq$ 30°	2.9°	Pass
	Impact Indicator	One Indicator Shall Deploy	Permanently Deployed	Pass
	Harness Stretch	Shall Not Exceed 18"	9.8"	Pass

### FallTech Test Report

<b>Test Report No.</b>	PC-2822	<b>Rpt. Date</b>	4/24/2023	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Zachary Winters	<b>Test Specification(s)</b>	ANSI Z359.11-2021: 4.3.3, 4.3.4, 4.3.5, 4.3.6				
<b>Part No.</b>	8127BM	<b>Part No. Revision</b>	C				
<b>Part Description</b>	FT-One FBH 3D Construction Belted, Medium, TB Legs / QC Chest						
<b>Test Request No.</b>	PC-2822	<b>Date Complete</b>	4/24/2023				

### Test Summary Continued

Test Specification	Test Criteria	Test Result	Pass/Fail
ANSI Z359.11-2021 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact $\geq$ 3,600 Lbf or 72" Free Fall 3137.9 Lbf	72" Free fall Pass
	Fall Arrest	Shall Not Release Torso Did Not Release	Pass
	Post Drop Angle	Angle at Rest $\leq$ 30° 3.5°	Pass
	Impact Indicator	One Indicator Shall Deploy Permanently Deployed	Pass
ANSI Z359.11-2021 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact $\geq$ 3,600 Lbf or 72" Free Fall 1982.7 Lbf	72" Free fall Pass
	Fall Arrest	Shall Not Release Torso Did Not Release	Pass
	Post Drop Angle	Angle at Rest $\leq$ 30° 5.1°	Pass
	Impact Indicator	One Indicator Shall Deploy Permanently Deployed	Pass
ANSI Z359.11-2021 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact $\geq$ 3,600 Lbf or 72" Free Fall 2103.8 Lbf	72" Free fall Pass
	Fall Arrest	Shall Not Release Torso Did Not Release	Pass
	Post Drop Angle	Angle at Rest $\leq$ 30° 4.4°	Pass
	Impact Indicator	One Indicator Shall Deploy Permanently Deployed	Pass
ANSI Z359.11-2021 4.3.6	Fall Arrest Indicator Test (Doral D-ring)	At Least One Fall Arrest Indicator Shall Deploy Visibly and Permanently Deployed	Pass
ANSI Z359.11-2021 4.3.6	Fall Arrest Indicator Test (Doral D-ring)	At Least One Fall Arrest Indicator Shall Deploy Visibly and Permanently Deployed	Pass
ANSI Z359.11-2021 4.3.6	Fall Arrest Indicator Test (Doral D-ring)	At Least One Fall Arrest Indicator Shall Deploy Visibly and Permanently Deployed	Pass

### Conclusion

Based upon the samples provided to the Lab:  
 FallTech P/N 8127BM Rev. C meets the requirements of ANSI Z359.11-2021

### Report Signatories and Approval

<b>Lab Quality Manager</b>		<b>Date</b>	4/24/2023
----------------------------	---	-------------	-----------