

FallTech FT-Lineman Pro Body Belt with Waist Pad

Specification Sheet | SKU 8050X | FallTech

Features

- Belt design prioritizes ergonomics and adjustability to support the climber's weight and eliminate pinch points.
- Features 4kV rated dielectric overmolded D-rings for secondary connection, protected from arc flash and electrocution hazards.
- Fully adjustable; accommodating a range of six D-ring sizes per belt size for that perfect fit.
- Optimized Primary Connecting Links maintain proper orientation of both carabiner and climber while still traveling smoothly.
- Features tongue buckle style belt connection.
- Meets ASTM F887 Standards and OSHA Regulations.



Technical Specifications

Type	Utility Lineman Body Belt
SKU	8050X
OSHA User Capacity	420 lb max.
ASTM User Capacity	420 lb max.
Belt	Premium Leather
Primary Connecting Links	Plated Alloy Steel; 5,000 lb min. static strength with 3,600 lb gate strength
D-rings	Overmolded alloy steel; 5,000 lb min. static strength
Buckles and Adjusters	Overmolded alloy steel; 3,372 lb min. static strength
Available Configurations	8050S (Small, Tongue Buckle), 8050M (Medium, Tongue Buckle), 8050L (Large, Tongue Buckle), 8050XL (X-Large, Tongue Buckle), 8050QCS (Small, Quick Connect), 8050QCM (Medium, Quick Connect), 8050QCL (Large, Quick Connect), 8050QCXL (X-Large, Quick Connect)
Standards	ASTM F887-20; OSHA 1926.502, 1926.954, and 1910.268
Warranty	FallTech 2-year limited warranty against defects in materials and workmanship

Fall Protection Distributors, LLC | standingseamroofanchor.com | 863-703-4522 | Distributor spec sheet compiled from FallTech published data.