

FallTech 8060B Arc Flash Nomex 4D Cross-over Climbing Harness

Specification Sheet | SKU 8060B | FallTech Body Wear

Features

- Features premium dielectric overmolded alloy steel dorsal, hip and sternal D-rings and mating buckle leg, chest and torso adjusters
- Arc resistant Nomex® webbing with Kevlar® fiber core throughout shoulders, torso, and legs.
- Includes paired lanyard parking keepers and Nomex® label cover
- Meets OSHA 1926.502 and 1910.66 Regulations



Technical Specifications

Product Type	Non-Belted Full Body Harness
D-Rings	4 D-Rings: Dorsal, Hip, Sternal
Adjustment	Mating Buckle Leg Adjustment
Webbing	Nomex®/Kevlar®; 5,000 lb min. static strength
D-Ring Hardware	Overmolded Alloy Steel; 5,000 lb min. static strength
Buckles and Adjusters	Overmolded alloy steel; 3,372 lb min. static strength
Static Strength	3,600 lb min.
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 425 lb max.
Standards	OSHA 1926.502 and 1910.140
Available Configurations	8060B (UniFit (S, M, L))
Warranty	FallTech 2-Year Manufacturer Warranty

Fall Protection Distributors, LLC | standingseamroofanchor.com | 863-703-4522 | Distributor spec sheet compiled from FallTech published data.