

FallTech 8063B Arc Flash Nylon 4D Cross-over Climbing Harness

Specification Sheet | SKU 8063B | FallTech Body Wear

Features

- Features premium dielectric overmolded alloy steel dorsal, hip and sternal D-rings and mating buckle leg, chest, and torso adjusters
- Nylon webbing throughout shoulders, torso, and legs provides economical level of arc flash resistance.
- Includes paired lanyard parking keepers and Nomex® label cover
- Meets ASTM F887 Standards
- Complies with ANSI Z359.11-2014



Technical Specifications

Product Type	Non-Belted Full Body Harness
D-Rings	4 D-Rings: Dorsal, Hip, Sternal
Adjustment	Mating Buckle Leg Adjustment
Webbing	Nylon; 5,000 lb min. static strength
D-Ring Hardware	Overmolded Alloy Steel; 5,000 lb min. static strength
Buckles and Adjusters	Overmolded alloy steel; 3,372 lb min. static strength
Static Strength	3,600 lb min.
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 425 lb max.
Standards	ANSI Z359.11-2014; ASTM F887; OSHA 1926.502 and 1910.66
Available Configurations	8063B (UniFit (S, M, L))
Warranty	FallTech 2-Year Manufacturer Warranty

Fall Protection Distributors, LLC | standingseamroofanchor.com | 863-703-4522 | Distributor spec sheet compiled from FallTech published data.