

FallTech 8070 Arc Flash Nomex 3D Belted Harness

Specification Sheet | SKU 8070 | FallTech Body Wear

Features

- Features premium dielectric overmolded alloy steel dorsal and hip D-rings and mating buckle torso adjusters
- Economical dielectric leather insulated alloy steel quick-connect leg, chest, and belt buckles also included.
- Arc resistant Nomex® webbing with Kevlar® fiber core throughout shoulders, torso, belt, and legs
- Shoulder yoke, sub-pelvic leg, and 6" waist support positioning pads feature ripstop and quilted Nomex® fabrics for advanced Arc Flash protection
- Quick-connect buckles feature visual indicators showing positive connection
- Includes paired lanyard parking keepers and Nomex® label cover
- Meets ASTM F887 Standards



Technical Specifications

Product Type	Construction Belted
D-Rings	3 D-Rings: Dorsal, Hip
Adjustment	Quick-Connect Leg Adjustment
Webbing	Nomex®/Kevlar®; 5,000 lb min. static strength
D-Ring Hardware	Overmolded Alloy Steel; 5,000 lb min. static strength
Buckles and Adjusters	Overmolded and plated alloy steel; 3,372 lb min. static strength
Static Strength	3,600 lb min.
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 425 lb max.
Standards	ANSI Z359.11-2014; OSHA 1926.502 and 1910.140; ASTM F887
Available Configurations	8070RS (Small), 8070M (Medium), 8070L (Large), 8070XL (XL)
Warranty	FallTech 2-Year Manufacturer Warranty

Fall Protection Distributors, LLC | standingseamroofanchor.com | 863-703-4522 | Distributor spec sheet compiled from FallTech published data.