

FallTech 8074FDQC Arc Flash Nomex 4D Construction Climbing

Specification Sheet | SKU 8074FDQC | FallTech

Features

- Features premium dielectric overmolded alloy steel dorsal, sternal, and hip D-rings, quick-connect leg, belt, and chest buckles, and torso adjusters.
- Arc resistant Nomex® webbing with Kevlar® fiber core throughout shoulders, torso, belt, and legs.
- Shoulder yoke, sub-pelvic leg, and 6" waist support positioning pads feature ripstop and quilted Nomex® fabrics for advanced Arc Flash protection.
- Overmolded quick-connect buckle feature visual indicator showing positive connection.
- Includes paired lanyard parking keepers and Nomex® label cover.
- Includes Arc Flash rated Suspension Trauma Relief Straps.



Technical Specifications

Type	Belted Full Body Harness
SKU	8074FDQC
Family	Arc Flash
D-Rings	4 (Dorsal, Hip, and Sternal)
Closures	Quick-connect Legs and Chest
Webbing	Nomex®/Kevlar®
Static Strength	3,600 lb min.
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 425 lb max.
Standards	ANSI Z359.11-2021; OSHA 1926.502 and 1910.140; ASTM F887-20
Available Configurations	8074FDQCXS (XS), 8074FDQCS (S), 8074FDQCM (M), 8074FDQCL (L), 8074FDQCXL (XL), 8074FDQC2X (2X), 8074FDQC3X (3X)
Warranty	FallTech 2-year manufacturer warranty, honored through Fall Protection Distributors

Fall Protection Distributors, LLC | standingseamroofanchor.com | 863-703-4522 | Distributor spec sheet compiled from FallTech published data.