

FallTech 8076FR Arc Flash Nomex Climbing Harness 1D+FD

Specification Sheet | SKU 8076FR | FallTech Body Wear

Features

- Features premium dielectric overmolded alloy steel dorsal D-ring and mating buckle torso adjusters
- Economical dielectric leather insulated quick-connect leg and chest buckles also included.
- Arc resistant Nomex® webbing with Kevlar® fiber core throughout shoulders, torso and legs
- Quick-connect buckles feature visual indicators showing positive connection
- Includes paired lanyard parking keepers and Nomex® label cover
- Meets ASTM F887 Standards
- Complies with ANSI Z359.11-2014



Technical Specifications

| | |
|---------------------------------|--|
| Product Type | Non-Belted Full Body Harness |
| D-Rings | 1 D-Ring: Dorsal |
| Adjustment | Quick-Connect Leg Adjustment |
| Webbing | Nomex®/Kevlar®; 5,000 lb min. static strength |
| D-Ring Hardware | Overmolded Alloy Steel; 5,000 lb min. static strength |
| Buckles and Adjusters | Overmolded and plated alloy steel; 3,372 lb min. static strength |
| Static Strength | 3,600 lb min. |
| ANSI User Capacity | 130 to 310 lb max. |
| OSHA User Capacity | 130 to 425 lb max. |
| Standards | ANSI Z359.11-2014; OSHA 1926.502 and 1910.140; ASTM F887 |
| Available Configurations | 8076FRS (Small), 8076FRM (Medium), 8076FRL (Large), 8076FRXL (XL), 8076FR2X (2X) |
| Warranty | FallTech 2-Year Manufacturer Warranty |

Fall Protection Distributors, LLC | standingseamroofanchor.com | 863-703-4522 | Distributor spec sheet compiled from FallTech published data.