

# FallTech 8076R3X Arc Flash 1D Standard Non-belted Rescue Harness

Specification Sheet | SKU 8076R3X | FallTech Body Wear

## Features

- Features premium dielectric overmolded alloy steel dorsal D-ring and mating buckle torso adjusters
- Economical dielectric leather insulated quick-connect leg and chest buckles also included.
- Includes integrated frontal rescue loops constructed with reinforced Nomex®
- Arc resistant Nomex® webbing with Kevlar® fiber core throughout shoulders, torso, and legs
- Quick-connect buckles feature visual indicators showing positive connection
- Includes paired lanyard parking keepers and Nomex® label cover
- Meets ASTM F887 Standards



## Technical Specifications

<b>Product Type</b>	Non-Belted Full Body Harness
<b>D-Rings</b>	1 D-Ring: Dorsal
<b>Adjustment</b>	Quick-Connect Leg Adjustment
<b>Webbing</b>	Nomex®/Kevlar®; 5,000 lb min. static strength
<b>D-Ring Hardware</b>	Overmolded Alloy Steel; 5,000 lb min. static strength
<b>Buckles and Adjusters</b>	Overmolded and plated alloy steel; 3,372 lb min. static strength
<b>Static Strength</b>	3,600 lb min.
<b>ANSI User Capacity</b>	130 to 310 lb max.
<b>OSHA User Capacity</b>	130 to 425 lb max.
<b>Standards</b>	ANSI Z359.11-2014; OSHA 1926.502 and 1910.140; ASTM F887
<b>Available Configurations</b>	8076R3X (3X)
<b>Warranty</b>	FallTech 2-Year Manufacturer Warranty