

FallTech 8078FDQC Arc Flash Nomex 2D Climbing Harness

Specification Sheet | SKU 8078FDQC | FallTech

Features

- Features premium dielectric overmolded alloy steel dorsal and sternal D-rings, quick-connect leg and chest buckles, and torso adjusters.
- Arc resistant Nomex® webbing with Kevlar® fiber core throughout shoulders, torso, belt, and legs.
- Shoulder yoke and sub-pelvic leg pads feature ripstop and quilted Nomex® fabrics for advanced Arc Flash protection.
- Overmolded quick-connect buckle feature visual indicator showing positive connection.
- Includes paired lanyard parking keepers and Nomex® label cover.
- Includes Arc Flash rated Suspension Trauma Relief Straps.



Technical Specifications

Type	Non-Belted Full Body Harness
SKU	8078FDQC
Family	Arc Flash
D-Rings	2 (Dorsal and Sternal)
Closures	Quick-connect Legs and Chest
Webbing	Nomex®/Kevlar®
Static Strength	3,600 lb min.
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 425 lb max.
Standards	ANSI Z359.11-2021; OSHA 1926.502 and 1910.140; ASTM F887-20
Available Configurations	8078FDQCXS (XS), 8078FDQCS (S), 8078FDQCM (M), 8078FDQCL (L), 8078FDQCXL (XL), 8078FDQC2X (2X), 8078FDQC3X (3X)
Warranty	FallTech 2-year manufacturer warranty, honored through Fall Protection Distributors

Fall Protection Distributors, LLC | standingseamroofanchor.com | 863-703-4522 | Distributor spec sheet compiled from FallTech published data.