

FallTech 8079FDQC FT-Arc Flash 4D Construction Climbing Harness

Specification Sheet | SKU 8079FDQC | FallTech

Features

- Comfort Legs® lateral leg strap construction greatly improves mobility and comfort.
- Features premium dielectric overmolded alloy steel dorsal, sternal, and hip D-rings, quick-connect leg, belt, and chest buckles, and torso adjusters.
- Arc resistant Nomex® webbing with Kevlar® fiber core throughout shoulders, torso, belt, and legs.
- Shoulder yoke, sub-pelvic leg pads, and 6" waist support positioning pads feature ripstop and quilted Nomex® fabrics for advanced Arc Flash protection.
- Overmolded quick-connect buckle feature visual indicator showing positive connection.
- Includes paired lanyard parking keepers and Nomex® label cover.



Technical Specifications

Type	Belted Full Body Harness
SKU	8079FDQC
Family	Arc Flash
D-Rings	4 (Dorsal, Hip, and Sternal)
Closures	Quick-connect Legs and Chest
Webbing	Nomex®/Kevlar®
Static Strength	3,600 lb min.
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 425 lb max.
Standards	ANSI Z359.11-2021; OSHA 1926.502 and 1910.140; CSA Z259.10-2018
Available Configurations	8079FDQCXS (XS), 8079FDQCS (S), 8079FDQCM (M), 8079FDQCL (L), 8079FDQCXL (XL), 8079FDQC2X (2X), 8079FDQC3X (3X)
Warranty	FallTech 2-year manufacturer warranty, honored through Fall Protection Distributors

Fall Protection Distributors, LLC | standingseamroofanchor.com | 863-703-4522 | Distributor spec sheet compiled from FallTech published data.