

# FallTech 8079QC FT-Arc Flash 3D Belted Harness

Specification Sheet | SKU 8079QC | FallTech Body Wear

## Features

- Comfort Legs® lateral leg strap construction greatly improves mobility and comfort
- Features premium dielectric overmolded alloy steel dorsal and hip D-rings, quick-connect leg, belt, and chest buckles, and torso adjusters
- Arc resistant Nomex® webbing with Kevlar® fiber core throughout shoulders, torso, belt, and legs.
- Shoulder yoke, sub-pelvic leg pads, and 6" waist support positioning pads feature ripstop and quilted Nomex® fabrics for advanced Arc Flash protection
- Overmolded quick-connect buckle feature visual indicator showing positive connection
- Includes paired lanyard parking keepers and Nomex® label cover
- Includes Arc Flash rated Suspension Trauma Relief Straps



## Technical Specifications

<b>Product Type</b>	Belted Full Body Harness
<b>D-Rings</b>	3 D-Rings: Dorsal, Hip
<b>Adjustment</b>	Quick-Connect Leg Adjustment
<b>Webbing</b>	Nomex®/Kevlar®; 5,000 lb min. static strength
<b>D-Ring Hardware</b>	Overmolded Alloy Steel; 5,000 lb min. static strength
<b>Buckles and Adjusters</b>	Overmolded alloy steel; 3,372 lb min. static strength
<b>Static Strength</b>	3,600 lb min.
<b>ANSI User Capacity</b>	130 to 310 lb max.
<b>OSHA User Capacity</b>	130 to 425 lb max.
<b>Standards</b>	ANSI Z359.11-2021; OSHA 1926.502 and 1910.140; CSA Z259.10-2018
<b>Available Configurations</b>	8079QCXS (XS), 8079QCS (S), 8079QCM (M), 8079QCL (L), 8079QCXL (XL), 8079QC2X (2X), 8079QC3X (3X)
<b>Warranty</b>	FallTech 2-Year Manufacturer Warranty

Fall Protection Distributors, LLC | [standingseamroofanchor.com](http://standingseamroofanchor.com) | 863-703-4522 | Distributor spec sheet compiled from FallTech published data.