

FallTech 8081 Arc Flash Belted Looped Harness

Specification Sheet | SKU 8081 | FallTech Body Wear

Features

- New wishbone shaped shoulder yoke reduces neck irritation and improves comfort
- Features economical dielectric dorsal loop, leather insulated alloy steel hip D-rings, quick-connect leg, chest and belt buckles, and mating buckle torso adjusters
- Nylon webbing throughout shoulders, torso, belt, and legs provides economical level of arc flash resistance.
- Shoulder yoke, sub-pelvic leg, and 6" waist support positioning pads feature ripstop and quilted Nomex® fabrics for advanced Arc Flash protection
- Features 1-1/4" Nomex® dorsal loop for Fall Arrest
- Quick-connect buckles feature visual indicators showing positive connection
- Includes paired lanyard parking keepers and Nomex® label cover



Technical Specifications

Product Type	Belted Full Body Harness
D-Rings	3 D-Rings: Dorsal Loop, Hip
Adjustment	Quick-Connect Leg Adjustment
Webbing	Nylon; 5,000 lb min. static strength
D-Ring Hardware	Nomex® Web Loop and Plated Alloy Steel; 5,000 lb min. static strength
Buckles and Adjusters	Plated alloy steel; 3,372 lb min. static strength
Static Strength	3,600 lb min.
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 425 lb max.
Standards	ANSI Z359.11-2014; ASTM F887; OSHA 1926.502 and 1910.66
Available Configurations	8081S (Small), 8081M (Medium), 8081L (Large), 8081XL (XL)
Warranty	FallTech 2-Year Manufacturer Warranty

Fall Protection Distributors, LLC | standingseamroofanchor.com | 863-703-4522 | Distributor spec sheet compiled from FallTech published data.