

FallTech 8087CFD Arc Flash Nylon Loop Overmold Hip Sternal

Specification Sheet | SKU 8087CFD | FallTech Body Wear

Features

- Features economical dielectric leather insulated alloy steel quick-connect leg and chest buckles and mating buckle torso adjusters
- Nylon webbing throughout shoulders, torso, and legs provides economical level of arc flash resistance.
- Features 1-1/4" Nomex® dorsal loop for Fall Arrest
- Quick-connect buckles feature indicators for positive visual engagement
- Includes paired lanyard parking keepers and Nomex® label cover



Technical Specifications

Product Type	Non-Belted Full Body Harness
D-Rings	1 D-Ring: Dorsal Loop
Adjustment	Quick-Connect Leg Adjustment
Webbing	Nylon; 5,000 lb min. static strength
D-Ring Hardware	Kevlar® Web Loop; 5,000 lb min. static strength
Buckles and Adjusters	Plated alloy steel; 3,372 lb min. static strength
Static Strength	3,600 lb min.
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 425 lb max.
Standards	ANSI Z359.11-2014; ASTM F887; OSHA 1926.502 and 1910.66
Available Configurations	8087CFDS (Small), 8087CFDM (Medium), 8087CFDL (Large), 8087CFDXL (XL), 8087CFD2X (2X)
Warranty	FallTech 2-Year Manufacturer Warranty

Fall Protection Distributors, LLC | standingseamroofanchor.com | 863-703-4522 | Distributor spec sheet compiled from FallTech published data.